



Geotechnical Data Report Bayou De Cade Marsh Creation and Ridge Restoration (TE-0138) Terrebonne Parish, Louisiana

Fugro Project No. 04.55174066 June 2018



Report No. 04.55174047 June 8, 2018

COASTAL PROTECTION AND RESTORATION AUTHORITY

8404 River Road Geismar, Louisiana 70734

Attention: Ms. April Newman

CPRA Task Manager

DRAFT Geotechnical Data Report Bayou De Cade Marsh Creation and Ridge Restoration (TE-0138) Terrebonne Parish, Louisiana

Fugro USA Land, Inc. (Fugro) is pleased to submit this geotechnical data report for the referenced project. Fugro's services were authorized by the State of Louisiana Coastal Protection and Restoration Authority (CPRA) on March 5, 2018 under Contract No. 440010495. This study was performed in general accordance with Fugro's Proposal No. 04.55174066_rev2, dated December 19, 2017.

As of June 8, 2018, there are a few pending test results pertaining to the consolidation tests, i.e., Atterberg limits and specific gravities. They will be added to the final report.

We appreciate the opportunity to be of service to CPRA and look forward to working together on the next phase of the project. Please call if you have any questions about this report.

Sincerely, **FUGRO USA LAND, INC.**

Samuel M. Bryant, P.E. Eric Marx, P.E. Vice President Vice President

Copies Submitted: pdf to addressee



CONTENTS

	Page
1. INTRODUCTION	4
1.1 Project Description	4
1.2 Purposes and Scope	4
1.3 Authorization and Personnel	4
1.4 Report Applicability	4
2. FIELD EXPLORATION	5
3. LABORATORY TESTING	5
4. GEOLOGY AND SUBSURFACE CONDITIONS4.1 Site Description	5
4.2 Geographic Information System Database	5
4.3 Subsurface Conditions	5
5. REFERENCES	6



ILLUSTRATIONS

	<u>Plate</u>
Vicinity Map	1
Site Layout and Exploration Plan	2
Cross-Sections	3a to 3d
APPENDIC	ES
Field Exploration	Appendix A
Laboratory Testing	Appendix B
Column Settling Tests	Appendix B1



1. INTRODUCTION

1.1 Project Description

The Louisiana Coastal Protection and Restoration Authority (CPRA) is planning to restore 11,276 linear feet of ridge habitat along the northern bank of Bayou De Cade and create/nourish approximately 504 acres of marsh by pumping hydraulically dredged material from Lake De Cade to the designated fill sites.

The site is located as shown on Plate 1. A site layout is presented as Plate 2. The project site is located in Terrebonne Parish, Louisiana, about 12 miles west of Dulac and immediately west of Lake De Cade. Approximate project area center coordinates are N29°22'37.23" and W90°55'00.39" (RE: NAD83). Elevations noted herein are based on the 1983 North American Vertical Datum (NAVD83). The land owner for the marsh creation area is Apache Louisiana Minerals LLC.

1.2 Purposes and Scope

The purpose of the geotechnical data study was to: 1) explore and evaluate subsurface soil conditions, and 2) perform laboratory testing to develop pertinent engineering parameters for marsh restoration.

1.3 Authorization and Personnel

Ms. April Newman is the CPRA task manager. Mr. Eric Marx, P.E., is the Fugro Project Manager, and Mr. Sam Bryant, P.E., is the Fugro technical lead. Mr. Ryan Fasone, with Fugro, coordinated field exploration. Exploration location and magnetometer survey services were provided by Fugro's survey group in Lafayette, Louisiana, with Mr. Jesse Kibodeaux, as the survey manager. Dr. William Moe, Ph.D, P.E., Principal/Manager, with SCTCS Group LLC, performed the column settling tests

1.4 Report Applicability

Explorations, laboratory testing, findings, and conclusions presented in this data report are based on the project description, as described herein, and the authorized scope of work.

If there are differences or changes in project location or design features from those described herein, Fugro should be authorized to review changes and propose additional exploration and laboratory testing, if deemed appropriate. Observations, conclusions, and recommendations may not apply to locations beyond explorations performed for this study and beyond project boundaries.

Fugro prepared this report exclusively for CPRA to guide geotechnical aspects of design and construction of proposed facilities. The study was conducted using the standard level of care and



diligence normally practiced by recognized engineering firms now performing similar services under similar circumstances in the area. This report, including all illustrations and appendices, should be used in its entirety. This report should be made available for information only and not as a warranty of subsurface conditions.

2. FIELD EXPLORATION

Field exploration, described in Appendix A, included fifteen (15) cone penetration test (CPT) soundings and fifteen (15) borings.

3. LABORATORY TESTING

Laboratory testing was performed to aid material classification, shear strength, compressibility and corrosion characteristics. Laboratory test results are presented in Appendix B. Column settling tests were performed on two selected composite samples. Test procedures and results are presented in Appendix B1.

4. GEOLOGY AND SUBSURFACE CONDITIONS

4.1 Site Description

Topographic and existing feature information is presented on Plate 2. Saucier (1994, Plate 14) indicate the site is underlain by Holocene Interdistributary deposits. Surficial conditions range from over water to within the marsh area and out in Lake DeCade, to just above water land surfaces around the marsh perimeter.

4.2 Geographic Information System Database

Information developed or obtained for the project was included in a geographic information system (GIS) databased using ESRI (2018) ArcGIS, version 10.4. Data from explorations, i.e., field and laboratory data, was included in a GIS database using Bentley Systems (2018) gINT, version 10. The gINT database file is linked to ArcGIS for processing. CPT electronic data files are included in the ArcGIS database.

4.3 Subsurface Conditions

4.3.1 Cross-Sections

Example subsurface profiles, presented as Plates 3a to 3d, generally show the distribution of subsurface conditions across the section lines. Profile locations are shown on Plate 2.



4.3.2 Earth Materials

Earth materials encountered in explorations consist mostly of soft clay with interbedded sand and silt layers. Organic and peat layers are also present. Comparing to Profile A-A', Profile B-B seems to indicate a more continuous sandy zone following along the profile line between about EI -13 and -5 ft or so.

4.3.3 Water Conditions

A nearby CRMS (2018) gauge CRMS0398-H01, located about 3/4-mile north of the marsh site center, indicates a mean water elevation of about El+0.65 ft, a range from about El-0.5 ft to as high as El+2.0 ft, and with a more typical range from about El+0.2 to El+1 ft for daily measurements between October 2016 to September/October 2017.

Wave action during field exploration was notable and affected water surface elevation measurements at exploration locations, see Table A-1 in Appendix A.

5. REFERENCES

Apache Louisiana Mineral LLC (2017) "Access Permit; Bayou Decade Ridge and Marsh Creation (TE-138), Terrebonne Parish, Louisiana," letter to Fugro USA Land, Inc., Attn: Mr. Mike Allen, P.G., November 10.

ASTM International (2017) "ASTM Compass, Section: 4 Construction," https://compass.astm.org.

Bentley Systems (2018) "gINT Professional, version 10," https://www.bentley.com/en.

Coastwide Reference Monitoring System (CRMS) (2018) https://www.lacoast.gov/crms_viewer2/default.aspx

ESRI (2018) "ArcGIS, version 10.4," https://www.esri.com/en-us/home.

Olson, R.E., Rauch, A.F., Mecham, E.C., and Luke, A.M. (2003) "Self-Weight Consolidation of Large Laboratory Deposits of Clay," Proceedings 12th Pan American Conference on Soil Mechanics and Geotechnical Engineering, MIT, Vol 1, pp. 703-708/

Robertson, P.K. and Cabal, K.L. (2015) "Guide to Cone Penetration Testing for Geotechnical Engineering, 6th Edition," prepared for Gregg Drilling & Testing, Inc.

Saucier, R.T. (1994) "Geomorphology and Quaternary Geologic History of the Lower Mississippi River Valley, Volumes I and II," prepared for The President Mississippi River Commission Vicksburg, Mississippi and US Army of Corps of Engineers, December.




U.S. Army Corps of Engineers (USACE) (1987) "Confined Disposal of Dredged Material," EM 1110-2-5027, September 30, *column settling testing described in Section 3-3 and Appendix B, Plans and Specifications*.

U.S. Army Corps of Engineers (USACE) (2015) "Dredging and Dredged Material Management," EM 1110-2-5025, July 31, supersedes EM 1110-2-5027, column settling testing described in Appendix G, Plans and Specifications and Appendix H, Column Settling Test Procedures.



PLATES





VICINITY MAP
Bayou Decade Marsh Creation and Ridge Restoration
Terrebonne Parish, Louisiana





Legend

▼ Fugro CPT

Fugro Boring

- Subsurface Profile Line Location

Project Area


Borrow Area

Topographic Survey Contours (Feet, NAVD88)

(survey data provided by client)

—-5— Contour interval is 5 feet

Contour interval is 1 foot




SITE LAYOUT AND EXPLORATION PLAN


Bayou Decade Marsh Creation and Ridge Restoration

Terrebonne Parish, Louisiana

















Legend

Fugro Boring Location




13 Field SPT N-Value

P Push

Soil Descriptions

Sandy Lean Clay (CL)

SOII	Descriptions	
	High-Plasticity Organic (OH)	Fat CLAY (CH)
****	Peat	Silt (ML)
	Lean CLAY (CL)	Silty SAND (SM)



Zone	Soil Behavior Type	U.S.C.S.
1 2 3 4 5 6 7 8	Sensitive Fine-grained Organic Material Clay to Silty Clay Clayey Silt to Silty Clay Silty Sand to Sandy Silt Sand to Silty Sand Gravelly Sand to Sand Sand to Clayey Sand	OL-CH OL-OH CL-CH MH-CL SM-ML SP-SM GP-SP SP-SC
9	Very Stiff Fine-grained*	CH-CL


*overconsolidated or cemented

SBT CORRELATION CHART ROBERTSON, 1990


SUBSURFACE PROFILE C-C'

Bayou Decade Marsh Creation and Ridge Restoration Terrebonne Parish, Louisiana





Legend





Fugro CPT

Field SPT N-Value

P Push

Sandy Lean Clay (CL)





Zone	Soil Behavior Type	U.S.C.S.
1	Sensitive Fine-grained	OL-CH
2	Organic Material	OL-OH
3	Clay to Silty Clay	CL-CH
4	Clayey Silt to Silty Clay	MH-CL
5	Silty Sand to Sandy Silt	SM-ML
6	Sand to Silty Sand	SP-SM
7	Gravelly Sand to Sand	GP-SP
8	Sand to Clayey Sand	SP-SC
9	Very Stiff Fine-grained*	CH-CL

*overconsolidated or cemented

SBT CORRELATION CHART ROBERTSON, 1990

SUBSURFACE PROFILE Borrow Area A

Bayou Decade Marsh Creation and Ridge Restoration Terrebonne Parish, Louisiana



APPENDIX A FIELD EXPLORATION



APPENDIX A - FIELD EXPLORATION

INTRODUCTION

This appendix provides information about field exploration, including drilling equipment and soil sampling methods. Field exploration was performed between March 26 and April 20, 2018.

Fugro performed 15 cone penetration test (CPT) soundings ranging in depth from 40 ft to 60 ft and 15 borings ranging in depth from 16 ft to 60 ft.

Table A-1 summarizes exploration locations, depths, ground surface elevations, and other information. Explorations are approximately located as shown on Plate 2. Explorations were located prior to commencement of the field exploration program.

As-drilled exploration locations and ground surface/mudline elevations were surveyed by Fugro's survey group.

FIELD COORDINATION

Exploration locations were cleared through Louisiana One Call. Apache Louisiana Minerals LLC (2017) provided access permission for Fugro exploration. Land owners were contacted prior to site mobilization, as necessary. The U.S. Army Corps of Engineers and U.S. Coast Guard were notified regarding field exploration.

Prior to drilling or CPT work, exploration locations were surveyed using a magnetometer assess the potential presence of pipelines or other magnetic-susceptible obstructions. A closed loop path was surveyed around each exploration location using a Geometrics 858 cesium vapor magnetometer. The loop path enclosed the exploration location and maintained a minimum 25-ft radius or a 25- by 25-foot rectangular cleared area. Cleared locations were marked with a cane pole or buoy with specific flagging.

Report No. 04.55174066 A-1

Table A-1. Exploration Summary

Exploration	LA State PI (NAD		NAD83 Ge			Completion		Depth to	Depth to Water Mudline Elevation	
ID	Easting	Northing	Latitude	Longitude	(IVAV DOO)	Date	Depth	Waamie	Licvation	
	ft	ft	deg	deg	ft		ft	ft	ft	
B-01	3,417,117.4	320,359.7	29.380211	-90.905437	-0.8	3/27/2018	60.0	1.3	0.5	
B-02	3,414,045.8	317,944.2	29.373600	-90.915109	-0.9	3/27/2018	60.0	2.2	1.3	
B-03	3,408,578.8	314,205.9	29.363374	-90.932314	-2.2	4/3/2018	60.0	3.2	1.0	
B-04	3,411,307.2	318,072.7	29.373980	-90.923705	-0.5	4/3/2018	40.0	1.4	0.9	
B-05	3,415,819.4	321,086.2	29.382222	-90.909504	-2.5	3/28/2018	40.0	3.0	0.5	
B-06	3,414,677.7	321,220.9	29.382604	-90.913087	-6.1	3/30/2018	60.0	7.0	0.9	
B-07	3,413,518.7	321,109.8	29.382310	-90.916728	-1.0	3/30/2018	40.0	1.9	0.9	
B-08	3,412,577.1	317,193.9	29.371551	-90.919729	-2.0	4/4/2018	40.0	2.5	0.5	
B-09	3,409,394.7	315,092.6	29.365804	-90.929743	-1.4	3/30/2018	40.0	2.0	0.6	
B-10	3,421,152.1	321,135.3	29.382302	-90.892760	-4.3	4/2/2018	16.0	6.0	1.7	
B-11	3,423,210.3	322,200.4	29.385209	-90.886285	-4.6	4/2/2018	16.0	6.0	1.4	
B-12	3,423,211.8	324,020.3	29.390213	-90.886258	-6.6	4/2/2018	16.0	8.0	1.4	
B-13	3,424,613.2	323,327.9	29.388294	-90.881866	-5.1	4/2/2018	16.0	6.5	1.4	
B-14	3,425,611.5	322,658.2	29.386442	-90.878740	-4.8	3/28/2018	16.0	6.5	1.7	
B-15	3,425,616.9	325,355.7	29.393859	-90.878689	-8.1	3/28/2018	18.0	9.0	0.9	
CPT-01	3,416,845.3	321,940.5	29.384561	-90.906273	-0.4	4/17/2018	40.0	1.0	0.6	
CPT-02	3,416,442.3	319,696.0	29.378393	-90.907565	-0.8	4/17/2018	60.0	1.5	0.7	
CPT-03	3,415,653.1	318,995.7	29.376475	-90.910051	-1.7	4/17/2018	40.0	2.0	0.3	
CPT-04	3,414,045.8	317,944.2	29.373600	-90.915109	-0.9	4/17/2018	60.0	2.2	1.3	
CPT-05	3,412,839.2	317,087.7	29.371257	-90.918907	-0.2	4/18/2018	60.0	1.0	0.8	
CPT-06	3,411,478.9	316,169.4	29.368745	-90.923188	-0.2	4/18/2018	40.0	1.0	0.8	
CPT-07	3,410,663.9	315,321.4	29.366421	-90.925756	-0.2	4/18/2018	40.0	1.0	0.8	
CPT-08	3,409,817.8	314,928.9	29.365350	-90.928416	-1.0	4/19/2018	60.0	1.5	0.5	
CPT-09	3,408,113.2	314,913.8	29.365325	-90.933768	-0.6	4/19/2018	60.0	1.5	0.9	
CPT-10	3,409,442.4	315,929.8	29.368106	-90.929584	-0.7	4/19/2018	40.0	1.5	0.8	
CPT-11	3,411,307.2	318,072.7	29.373980	-90.923705	-0.5	4/19/2018	40.0	1.4	0.9	
CPT-12	3,412,176.9	319,390.1	29.377594	-90.920960	-1.4	4/20/2018	40.0	1.5	0.1	
CPT-13	3,412,670.8	320,574.8	29.380848	-90.919396	-1.2	4/20/2018	60.0	1.5	0.3	
CPT-14	3,415,362.9	322,585.6	29.386350	-90.910920	-0.4	4/20/2018	40.0	1.2	0.8	
CPT-15	3,416,769.5	323,055.9	29.387629	-90.906498	-1.0	4/18/2018	40.0	2.0	1.0	

Report No. 04.55174066 A-2



CONE PENETRATION TEST SOUNDINGS

CPT Logs

CPT logs follow the appendix text, as Plates A-1 to A-15, along with a key for the CPT logs as Plate A-16. CPT logs present tip resistance, friction ratio (friction resistance/tip resistance), general soils type, pore pressure measured near by a transducer behind the cone tip, and interpreted strength properties.

Cone penetration test (CPT) soundings were conducted using an air boat mounted CPT rig. A CPT unit utilizes the self-weight of the equipment to push a cylindrical steel probe into the ground. CPT data is obtained by pushing a series of cylindrical rods, with an instrumented probe at the base, into the soil at a constant rate. The probe consists of a piezocone tip element and a side-friction sleeve element. Continuous measurements of penetration resistance at the cone tip, friction along the friction sleeve, and pore water pressure were recorded during the penetration tests. During testing, the results were saved electronically for further data reduction in our office.

CPT Hole Completion

CPTs were backfilled upon completion with cement-bentonite grout, using a tremie pipe and topped off at the surface.

BORINGS

Boring Logs

Boring logs are presented as Plates A-17 to A-32, with a key to terms and symbols presented as Plates A-32a and 32b. Boring logs present boring number, coordinates, ground surface/mudline elevation, completion date, logger's name, drilling method, drill rig type, backfill method, material descriptions, sampling method, and point-depth related laboratory test results.

Drilling Methods and Equipment

Borings were drilled with a Robicheaux Air Boat Drill Unit 38 (ABDU-38) drill rig, using wet rotary techniques.

Sampling Equipment and Methods

Cohesive soil samples were generally obtained at a maximum of 5-ft intervals. When sandy/cohesionless materials were encountered, samples were generally obtained at 3-ft-depth intervals for a depth interval of about 10 feet before proceeding with 5-ft-depth intervals. Sampling methods are described in Table A-2.

Report No. 04.55174066 A-3



Table A-2. Sampling Methods

Sampler Type	Dimensions	Description		
Thin-wall Tubes	3-inch-OD, 2-7/8-in-ID	Test procedure in general accordance with ASTM D1587. 30-inch-long, thin-wall tubes are attached to the drill string and hydraulically pushed into the borehole bottom about 24 inches (2 ft).		
Standard Penetration Test (SPT)	2-inch-OD, 1-3/8-inch-ID	Test procedure in general accordance with ASTM D1586. SPT split-spoon sampler, attached to drill pipe and lowered to borehole bottom, are driven with a cat head and 140-pound manual hammer attached to the top of the drill rod near the ground surface.		

A field technician logged the borings and samples in general accordance with the ASTM D2488 for visual soil classification. Boundaries between soil types shown on the logs are approximate and the transition between different soil layers may be gradational.

Tube samples were extruded in the laboratory with a hydraulic ram. After extrusion, samples were identified according to project number, boring number and depth, then wrapped in aluminum foil and placed in plastic bags to protect against moisture loss.


SPT samples were identified in the same manner as tube samples but were placed in plastic bags in the field and transported to the laboratory. Field SPT blows are recorded as the split-barrel sampler is advanced 18 inches. Blow counts are recorded for three successive 6-inch-depth intervals. Field N-values are calculated by adding the second and third blow count numbers. Field SPT N-values suggest relative density of cohesionless soils and relative consistency of cohesive soils.

Borehole Completion

Borings were backfilled upon completion with cement-bentonite grout using a tremie and topped off at the surface. Cuttings were spread out as the site.

Report No. 04.55174066 A-4






LOCATION: E: 3,416,845, N: 321,941, Louisiana State Plane South, NAD83, Feet SURFACE EL: -0.4ft +/- NAVD88

COMPLETION DEPTH: 41.00ft TESTDATE: 4/17/2018

LOG OF: CPT-01
Bayou Decade Marsh Creation
and Ridge Restoration
Terrebonne Parish, Louisiana






LOCATION: E: 3,416,442, N: 319,696, Louisiana State Plane South, NAD83, Feet SURFACE EL: -0.8ft +/- NAVD88

COMPLETION DEPTH: 61.01ft TESTDATE: 4/17/2018

LOG OF: CPT-02
Bayou Decade Marsh Creation
and Ridge Restoration
Terrebonne Parish, Louisiana






LOCATION: E: 3,415,653, N: 318,996, Louisiana State Plane South, NAD83, Feet SURFACE EL: -1.7ft +/- NAVD88

COMPLETION DEPTH: 41.33ft TESTDATE: 4/17/2018

LOG OF: CPT-03
Bayou Decade Marsh Creation
and Ridge Restoration
Terrebonne Parish, Louisiana






LOCATION: E: 3,414,046, N: 317,944, Louisiana State Plane South, NAD83, Feet

SURFACE EL: -0.9ft +/- NAVD88 COMPLETION DEPTH: 61.01ft TESTDATE: 4/17/2018

LOG OF: CPT-04
Bayou Decade Marsh Creation
and Ridge Restoration
Terrebonne Parish, Louisiana






LOCATION: E: 3,412,839, N: 317,088, Louisiana State Plane South, NAD83, Feet

SURFACE EL: -0.2ft +/- NAVD88 COMPLETION DEPTH: 61.01ft TESTDATE: 4/18/2018

LOG OF: CPT-05
Bayou Decade Marsh Creation
and Ridge Restoration
Terrebonne Parish, Louisiana



LOCATION: E: 3,411,479, N: 316,169, Louisiana State Plane South, NAD83, Feet SURFACE EL: -0.2ft +/- NAVD88


COMPLETION DEPTH: 41.00ft

TESTDATE: 4/18/2018

EXPLORATION METHOD: Cone Penetrometer
PERFORMED BY: Fugro
REVIEWED BY: S. Bryant
CONE AREA RATIO: 0.59

LOG OF: CPT-06
Bayou Decade Marsh Creation
and Ridge Restoration
Terrebonne Parish, Louisiana






LOCATION: E: 3,410,664, N: 315,321, Louisiana State Plane South, NAD83, Feet

SURFACE EL: -0.2ft +/- NAVD88 COMPLETION DEPTH: 41.00ft TESTDATE: 4/18/2018

LOG OF: CPT-07
Bayou Decade Marsh Creation
and Ridge Restoration
Terrebonne Parish, Louisiana






LOCATION: E: 3,409,818, N: 314,929, Louisiana State Plane South, NAD83, Feet

SURFACE EL: -1.0ft +/- NAVD88 COMPLETION DEPTH: 60.68ft TESTDATE: 4/18/2018

LOG OF: CPT-08
Bayou Decade Marsh Creation
and Ridge Restoration
Terrebonne Parish, Louisiana



SURFACE EL: -0.6ft +/- NAVD88

COMPLETION DEPTH: 61.07ft TESTDATE: 4/18/2018

LOG OF: CPT-09
Bayou Decade Marsh Creation


and Ridge Restoration
Terrebonne Parish, Louisiana

PERFORMED BY: Fugro

REVIEWED BY: S. Bryant

CONE AREA RATIO: 0.59






LOCATION: E: 3,409,442, N: 315,930, Louisiana State Plane South, NAD83, Feet

SURFACE EL: -0.7ft +/- NAVD88 COMPLETION DEPTH: 41.00ft TESTDATE: 4/18/2018

LOG OF: CPT-10
Bayou Decade Marsh Creation
and Ridge Restoration
Terrebonne Parish, Louisiana




LOCATION: E: 3,411,307, N: 318,073, Louisiana State Plane South, NAD83, Feet SURFACE EL: -0.5ft +/- NAVD88

COMPLETION DEPTH: 41.00ft TESTDATE: 4/18/2018

EXPLORATION METHOD: Cone Penetrometer PERFORMED BY: Fugro REVIEWED BY: S. Bryant CONE AREA RATIO: 0.59

LOG OF: CPT-11 Bayou Decade Marsh Creation and Ridge Restoration Terrebonne Parish, Louisiana





LOCATION: E: 3,412,177, N: 319,390, Louisiana State Plane South, NAD83, Feet

SURFACE EL: -1.4ft +/- NAVD88 COMPLETION DEPTH: 41.07ft TESTDATE: 4/20/2018


LOG OF: CPT-12
Bayou Decade Marsh Creation

and Ridge Restoration
Terrebonne Parish, Louisiana

EXPLORATION METHOD: Cone Penetrometer PERFORMED BY: Fugro REVIEWED BY: S. Bryant CONE AREA RATIO: 0.59

PLATE A-12






LOCATION: E: 3,412,671, N: 320,575, Louisiana State Plane South, NAD83, Feet SURFACE EL: -1.2ft +/- NAVD88

COMPLETION DEPTH: 61.01ft TESTDATE: 4/20/2018

LOG OF: CPT-13
Bayou Decade Marsh Creation
and Ridge Restoration
Terrebonne Parish, Louisiana






LOCATION: E: 3,415,363, N: 322,586, Louisiana State Plane South, NAD83, Feet SURFACE EL: -0.4ft +/- NAVD88

COMPLETION DEPTH: 41.07ft TESTDATE: 4/20/2018

LOG OF: CPT-14
Bayou Decade Marsh Creation
and Ridge Restoration
Terrebonne Parish, Louisiana






LOCATION: E: 3,416,770, N: 323,056, Louisiana State Plane South, NAD83, Feet SURFACE EL: -1.0ft +/- NAVD88

COMPLETION DEPTH: 41.07ft TESTDATE: 4/18/2018

LOG OF: CPT-15
Bayou Decade Marsh Creation
and Ridge Restoration
Terrebonne Parish, Louisiana





Zone	Soil Behavior Type	U.S.C.S.
1 2 3 4 5 6 7 8 9	Sensitive Fine-grained Organic Material Clay Silty Clay to Clay Clayey Silt to Silty Clay Sandy Silt to Clayey Silt Silty Sand to Sandy Silt Sand to Silty Sand Sand	OL-CH OL-OH CH CL-CH MH-CL ML-MH SM-ML SM-SP SW-SP SW-GW
11 12	Gravelly Sand to Sand Very Stiff Fine-grained * Sand to Clayey Sand *	CH-CL SC-SM

^{*}overconsolidated or cemented

SBT CORRELATION CHART (Robertson and Campanella, 1988)

KEY TO CPT LOGS

Bayou Decade Marsh Creation and Ridge Restoration Terrebonne Parish, Louisiana

				LOCATION: See Plate 1			CL/	ASSIF	ICAT	ION			SHE	AR S	TRENG	TH
DEPTH, FT	WATER LEVEI	SYMBOL	BLOWS PER FOOT	COORDINATES: N 29° 22' 48.77" W 90° 54' 19.56" SURFACE EL.: -0.8' STRATUM DESCRIPTION	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	◇ To △ Ha		ne IPS PE	Miniatur ER SQ FT	
				SILTY SAND (SM), dark gray, with clay seams and	.							0	.5 1	.0 1	.5 2.0	2.5
 - 5 —				shells LEAN CLAY WITH SAND (CL), soft, gray - very soft, with shells at 2' - with a 1' layer of SILTY SAND at 3' - with organics below 3' firm below 4'	- 1.0 - 5.5	- - - -	74	30 33 28	37 35	22 19	15 _ - 16 -	A	l			
 -10 		X	N=25	SILTY SAND (SM), dark gray, with organics, and clay partings and pockets - with a 1" peat seam at 6' - medium-dense, gray below 8'	40.2	- - -		23 21			- -	<i< td=""><td>•</td><td></td><td></td><td></td></i<>	•			
			N=20	SANDY LEAN CLAY (CL), very stiff, gray	+ 10.3	-		24			-					
 -15 -				LEAN CLAY (CL), very soft, gray, with shells	+ 12.0	- - -		26			- -	▲ □				
			N=13	- stiff below 16'		-		27	43	21	22 .					
 20 				FAT CLAY (CH), very soft to soft, gray, with sand pockets, organics, and shells	+ 18.0	- 79 - -		44			-	•				
 25 				ORGANIC CLAY (OH), firm, black and gray, with few peat pockets and seams	23.0	- - - -		116	126	34	92 -	- 🗆 🗘	A			
 - 30 - 	. !			PEAT (PT), firm, black	- 28.0	- - - -		321	473	321	152 -	-		⋄ □		A
 - 35 - 				FAT CLAY (CH), soft to firm, gray - with sand lenses and pockets at 33'	- 33.0	- 80 -		41			-					
 40 				- with sand partings at 38'		- - 69 -		59			- - -	- 🕬	•			
				- with sand lenses at 43'		_		57			-					
NOTE 1		erms a	and symb	ools defined on Plates A-32a and A-32b.					TOTA CAVE DRY WET BACK LOGG DRIL	AL DE ED DE AUGE ROTA (FILL: GER: L RIG	ION D PTH: EPTH: ER: N ARY: Cem R. Fa EX: ABE TYPE:	ATE: 60.0' Not App of App 0' to 6 nent-B isone	Marc Applic Dicab 60' entor	able le	, 2018 rout	
f	ī	G	20	Bayou De Cade Marsh Creation a Restoration	nd Ri	dge			LC)G (OF E	BOR	RINC	3 N	О. В	-01
V				(TE-0138, Task 1)												
				Terrebonne Parish, Louisiana			Proj	ect No).						E A-	

						LOCATION: See Plate 1			CLA	ASSIF	ICAT	ION			SHE	AR S	TREN	GTH	
DEPTH, FT		WATER LEVEI	SYMBOL	SAMPLES	BLOWS PER FOOT	COORDINATES: N 29° 22' 48.77" W 90° 54' 19.56" SURFACE EL.: -0.8'	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦To	netron rvane ind Va	ne	Ur Miniat ER SQ F		ial 🗨
		1		\perp		STRATUM DESCRIPTION								0	.5 1	.0 1	.5 2.	0 2.	5
- - - -50 - - - -	-					FAT CLAY (CH), soft to firm, gray - with few sand pockets at 48'		- - - - - - - - - - -		59 67	82	27	- - 55 - - - - -						
- - - - 60	- - -					- with shell traces and shell fragments below 58'	- 60.0	- - - -		37	96	27	- - 69 -		^				
- - - - - - - - - - - - - - - - - - -																			
FCBR_LOG (FINAL) 2016 04.55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18			erms	s ar	nd symb	COMPLETION DATE: March 26, 2018 TOTAL DEPTH: 60.0' CAVED DEPTH: Not Applicable DRY AUGER: Not Applicable WET ROTARY: 0' to 60' BACKFILL: Cement-Bentonite Grout LOGGER: R. Fasone DRILL RIG: ABDU-38 HAMMER TYPE: Manual Bayou De Cade Marsh Creation and Ridge Restoration COMPLETION DATE: March 26, 2018 TOTAL DEPTH: 60.0' CAVED DEPTH: Not Applicable WET ROTARY: 0' to 60' BACKFILL: Cement-Bentonite Grout LOGGER: R. Fasone DRILL RIG: ABDU-38 HAMMER TYPE: Manual													
-INAL) 2016	I	u	G	k	20	Bayou De Cade Marsh Creation and Ridge Restoration (TF-0138, Task 1)												1	
R_LOG (F	٧			$\hat{}$		(TE-0138, Task 1)			Proj	ect No			740		ים	Λ.Τ.	· ^	. 17	'h
S S						Terrebonne Parish, Louisiana 04.55174066 PLATE A-1									\- I /	Ŋ			

			LOCATION, Con Plate 4			CL/	ASSIF	ICAT	ION			SHE	AR S	TREN	GTH	_
ОЕРТН, FT	WATER LEVEL SYMBOL SAMPLES	BLOWS PER FOOT	LOCATION: See Plate 1 COORDINATES: N 29° 22' 24.77" W 90° 54' 54.11" SURFACE EL.: -0.9'	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	□Pe	enetrom rvane and Var	neter ne	Un	confined Triaxia ure Vand	•
	W (՝	STRATUM DESCRIPTION		\ <u>\</u>	PA8 200	8			చ ≤	0			R SQ F	T) 2.5	
			LEAN CLAY (CL), very soft, dark gray, with peat pockets, sand pockets and roots		-		67			-						
				4.0	-		36	39	23	16 -	▲ ♦					
-5 -			SANDY LEAN CLAY (CL), soft to firm, dark gray, with roots	6.0	_	60	28			_	♦ [
		N=7	SILTY SAND (SM), loose, gray		-		32			-						
 -10 -		N=9			-	33	34			-						
		N=3	- very loose below 10.5' - with clay pockets below 12'		-		32			-						
		N=2	FAT CLAY (CH), very soft, gray - gray and dark gray, with organics from 14' to 18'	13.5	-		7.4	404	20	-						
-15 - 			- firm at 16'		-		74 76	121	36	85 -		•				
			- soft at 18' - with 2" sand layer at 18'		- - 59		67			-	•					
-20 - 			,		-					-						
			150000000000000000000000000000000000000	24.0						-						
25 			LEAN CLAY (CL), soft to very soft, gray -with an organic layer at 24'		-		163	39	19	20_	- ^					
			- with peat layers at 28'		- - - 75		29			-		♦				
- 30			- with a 2" sand layer at 30'		- -		20			-	-					
			SILT (ML), gray, with clay seams	33.0						-						
 -35 -			one i (ine), gray, mai oray occanic		-		34			_		>				
8					-					-						
- 40 —					-	99	41			-	(24)					
2610.GD				+ 43.0	-					-						
ATE 04			LEAN CLAY (CL), firm, gray, with sand layers	43.0			48	34	20	14 -		•				_
04.55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18		and syml	bols defined on Plates A-32a and A-32b.					TOTA CAVE DRY WET BACK LOGG DRIL	AL DE ED DE AUGE ROTA (FILL: GER: L RIG	ION D PTH: EPTH: ER: N ARY: Cem R. Fa : ABE TYPE:	60.0' Not Apport Apport to 6 ent-Besone DU-38	Applicablicablicable 60' enton	able e			
L) 2016 04	ugi	20	Bayou De Cade Marsh Creation a Restoration	nd Ri	dge			LC)G	OF E	BOF	RINC	3 N	O. E	3-02	_
G (FINAL			(TE-0138, Task 1)													
FCBR_LOG (FINAL) 2016			Terrebonne Parish, Louisiana			Proj	ect No		.551	740	66	PL	.AT	E A	-18a	<u> </u>



						LOCATION: See Plate 1			CL	ASSIF	ICAT	ION			SHE	AR S	TREN	GTH	
ОЕРТН, FT		WATER LEVEI	SYMBOL		BLOWS PER FOOT	COORDINATES: N 29° 22' 24.77" W 90° 54' 54.11" SURFACE EL.: -0.9'	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦To	netron rvane ind Vai	ne	Miniat	nconfin Triax ure Va	dal 🌑
		≷			<u> </u>	STRATUM DESCRIPTION	_	3	PA 20	8			= ⊒	0			R SQ F		5
	-					LEAN CLAY (CL), firm, gray, with sand layers		-					-		.0 1			0 2.	
- - -50 -	-					FAT CLAY (CH), soft, gray - with some sand layers at 48'	+ 48.0	- 68 -		57			-	• • • • • • • • • • • • • • • • • • •	•				
- - - 55 -	-					- firm below 53'		- - - -		66			- - - -	- - ☑>	A				
- - - -60							- 60.0	- - - 		73 — —	100	28	72 - 	 	A				
- - - -65	-							- - -					-	-					
- - - -	-							- - -					- - -	-					
70 - - - -	_							_ - - -					- - -	-					
- 75 · - -	-							- - -					- - -	-					
- - 80 -	-							- - -					- - -	-					
- - - - - 85	-							- - -					- - -	-					
ATE 042610.GE								- - -					- - -						
FCBR_LOG (FINAL) 2016 04.55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18			erms	and	d symbo	ols defined on Plates A-32a and A-32b.	CAVED DEPTH: Not Applicable DRY AUGER: Not Applicable WET ROTARY: 0' to 60' BACKFILL: Cement-Bentonite Grout LOGGER: R. Fasone DRILL RIG: ABDU-38 HAMMER TYPE: Manual												
INAL) 2016	Í	u	G	R	0	Bayou De Cade Marsh Creation a Restoration	nd Ri	dge			LC	OG (OF E	BOR	RINC	3 N	O. I	3-02	2
CBR_LOG (F	۷			\sim		(TE-0138, Task 1) Terrebonne Parish, Louisiana			Proj	ect No	04.	.551	740	66	PL	_AT	E A	\-18	Bb
						Terrebonne Parish, Louisiana 04.55174066									_				

			LOCATION: See Plate 1			CL	ASSIF	ICAT	ION			SHEA	R ST	REN	GTH	
ОЕРТН, FT	WATER LEVEL SYMBOL SAMPLES	BLOWS PER FOOT	COORDINATES: N 29° 21' 48.14" W 90° 55' 56.36" SURFACE EL.: -2.2' STRATUM DESCRIPTION	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦ Тоі ∆ На	nd Vane	e PS PEF	Miniatu R SQ F	Г	al ● ne ▲
- ·			FAT CLAY (CH), gray, with peat and organics - with shells at 0'		- - -		65 31			- -	▲					
- 5 - 5		N=4 N=3 N=17	SILTY SAND (SM), very loose, gray - with clay pockets and wood at 4' - medium-dense below 8'	4.0	- - - - -	19	11			- - - -						
—10 — - -		N=21	LEAN CLAY (CL), soft to firm, gray	<u> </u>	- -	17	29			-						
- · · · · · · · · · · · · · · · · · · ·		ò	- with organic traces at 16' - with peat layers at 18'		- 86 - - - - 54 -		39 86 81 65	39	18	21 - 21 - -	•	•	•			
-20 - - · · - · · 25 -			ORGANIC CLAY (OH), brown and gray, with peat FAT CLAY (CH), soft, gray, with silt pockets and	23.0 24.2	_ - - - _ 58		69			- - -	•					
- · - ·			organics SILT (ML), gray, with clay and sand seams	28.0	- - -	87	28			-	♦					
-30 - - ·			FAT CLAY (CH), very soft, gray	+ 33.0	- - -					-						
- 35 - - 35 - 			- soft at 38'		- - - -	91	39			- - - -	*					
			- with sand layers from 38' to 43'		- 71 - - - -		53			- - - -						
NOT		and symb	ools defined on Plates A-32a and A-32b.					TOTA CAVE DRY	al de Ed de Auge	ION D. PTH: EPTH: ER: No	60.0' Not A ot App	opplica	ble	18		

WET ROTARY: 0' to 60'

BACKFILL: Cement-Bentonite Grout

LOGGER: R. Fasone DRILL RIG: ABDU-38 HAMMER TYPE: Manual



FCBR_LOG (FINAL) 2016 04.55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18

Bayou De Cade Marsh Creation and Ridge Restoration

LOG OF BORING NO. B-03

(TE-0138, Task 1)

Terrebonne Parish, Louisiana

Project No.

PLATE A-19a 04.55174066

	T_				LOCATION: See Plate 1			CL	ASSIF	ICAT	ION			SHE	AR S	TREN	GTH	
DEPTH, FT	WATER I EVE	SYMBOL	SAMPLES	BLOWS PER FOOT	COORDINATES: N 29° 21' 48.14" W 90° 55' 56.36" SURFACE EL.: -2.2'	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦To	netror rvane nd Va	ne	Miniat		ial 🌑
	>			В	STRATUM DESCRIPTION		5	PA 200	8			≧ ≦	٥			R SQ F		5
_					FAT CLAY (CH), very soft, gray		-					_	Ť					
- - - 50 -	- - - -				- firm, with few sand partings and trace organics at 48	ı	- - - 69 -		60			- - - -	\	•				
- - - 55 -	- - - -				- soft at 53'		- - - -			83	26	57 -	*					
- - - -60 -	-				- firm below 58'	- 60.0	- - - 59 -		70 — —			- - - -	\	•	<u> </u>			
FCBR_LOG (FINAL) 2016 04:55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18			s an	nd symb	COMPLETION DATE: April 3, 2018 TOTAL DEPTH: 60.0' CAVED DEPTH: Not Applicable DRY AUGER: Not Applicable WET ROTARY: 0' to 60' BACKFILL: Cement-Bentonite Grout LOGGER: R. Fasone DRILL RIG: ABDU-38 HAMMER TYPE: Manual													
L) 2016 04.5;	Fi	JG	IR	20	Bayou De Cade Marsh Creation and Ridge Restoration LOG OF BORING NO. B-03												3	
G (FINA					(TE-0138, Task 1)													
FCBR_LO			$\widehat{}$		Terrebonne Parish, Louisiana			Proj	ect No		.551	740	66	Pl	_AT	ΕA	\-19	b

					LOCATION: See Plate 1			CLA	ASSIF	ICAT	ION			SHE	AR S	ΓREN	GTH	
DEPTH, FT		WATER LEVEI	SYMBOL	BLOWS PER FOOT	COORDINATES: N 29° 22' 26.38" W 90° 55' 25.32" SURFACE EL.: -0.5'	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦To	enetron rvane and Var	ne	Ur Miniat R SQ F		dal 🌑
		>			STRATUM DESCRIPTION)	P 6	0				0			.5 2.		.5
-	4				FAT CLAY (CH), very soft, dark gray and gray - with peat layers at 0'		-		59	127	34	93 -	A					
-	1				- with organics from 2' to 8'		-		E1			-						
_	7				are with part layers at 41		F		54			-						
- 5	\dashv				- gray, with peat layers at 4'		F		50	60	18	42 -	4					
F	1				- soft, brown and gray, with silt pockets at 6'		85		41			-	•	▶▲				
-	+				 - gray below 8'		-					-						
- 10	_						Ĺ		52			_						
-	+						-		34			-	•					
_	1				- with silt lenses and partings below 12'		- 87		33			-	40					
-	+						-					-						
—15 -	╛						_		35			_	•					
ŀ	+				- soft, with organic traces below 16'		-		37			-	<▲					
ţ	1				LEAN CLAY (CL), soft, gray	18.0			34			_	(A)					
-20	\dashv						-					-						
F	1						-					-						
F	\exists				FAT CLAY (CH), very soft, gray	23.0												
- -25	_						- 84 -		38			_	• 🕫	1				
-	+						-					-						
ţ	1					28.0						-						
-	+				LEAN CLAY (CL), very soft, gray, with silt and sand pockets		-			30	20	10 -	♦					
-30 -	7						-					_						
ŀ	+						-					-						
F	7				- soft below 33'		- 79		45			-	•					
-35	\dashv						-					-						
_	7						F					-						
17/18	+				LEAN CLAY WITH SAND (CL), gray	38.0												
⁸ −40	4				SILTY SAND (SM), gray	48:8	<u> </u>						<u> </u>					
0.GD	+	[:]					-					-						
14261	4						-					-						
ATE (_						-					-	-					
NO NO	TE	<u>S:</u>							- 1			ION D		April	3, 20	18		
ITAT	1.	. Te	erms a	and symb	ools defined on Plates A-32a and A-32b.							PTH:		\nnlic	ahla			
00							CAVED DEPTH: Not Applicable DRY AUGER: Not Applicable											
FUGF							WET ROTARY: 0' to 40' BACKFILL: Cement-Bentonite Grout											
3PJ														entor	ite G	out		
1066.0												R. Fa						
.5517									- 1			TYPE:						
2016 04.		= -	_		Bayou De Cade Marsh Creation an Restoration	nd Ri	dge			LC)G (OF E	3OF	RINC	3 N	— Э. Е	3-04	4
(FINAL)	I	J		20	(TE-0138, Task 1)													
FCBR_LOG (FINAL) 2016 04.55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18	<u> </u>				Terrebonne Parish, Louisiana			Proj	ect No		551	740	66	F	PLA	TE	A-2	20
ú 🖳					I .													

					LOCATION: See Plate 1			CL	ASSIF	ICAT	ION			SHE	AR S	TREN	GTH	
ОЕРТН, FT	VATED EVE	WAIEKLEVE	SAMPLES	BLOWS PER FOOT	COORDINATES: N 29° 22' 56" W 90° 54' 34.17" SURFACE EL.: -2.5'	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦To	netrom rvane ind Var	ne	Miniat	Triax ure Va	ial 🌑
	3	≥		В	STRATUM DESCRIPTION		5	26 26	Ō			<u> </u>	0.			R SQ F		.5
	Ţ				FAT CLAY (CH), very soft to firm, dark gray		-		60	55	18	37 -	▲ >					
					- with a 2" organic clay layer at 2'		- - 71		52			-	•	•				ì
-5-]				- with roots below 4'		_		45	65	20	45 -		◇▲				
- ·					LEAN CLAY (CL), soft, gray - with roots at 6' - with sand pockets at 7'	6.0	- - -		32			-	♦					
- 10					- firm at 8' - very soft, with sand layers and ferrous nodules at 10)'	- 87 - -	95	33			- - -	A \$	•				1
 - 15 -			X	N=22	- very stiff, with organics at 12.5' - with silt pockets from 12.5' to 18'		- - - - 72		46 52	36	20	16 ⁻						
					- with wood at 16'		- '2 -		35			- -	⋄ ▲					1
- - -20 -			X	N=Push	- very soft, with sand pockets at 18'		-		32	31	22	9 -						
 25 					- firm, with wood and silt pockets below 23'		- - 89 - -		33			- - - - -	< ▲	•				
30 <u></u>		1/2	<u>//</u>		PEAT (PT), gray	29.0	<u> </u>		231						♦			A
	1	7					-					-						
- - -35 -				N=Push	LEAN CLAY (CL), soft, gray	+ 33.0	-		36	32	19	13 -						
					- soft, with silt pockets below 38'	- 40.0	- - - - -		42			- - - - 						- — -
TE 042610							- - -					- - -						
FCBR_LOG (FINAL) 2016 04.55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18		TOTAL DEPTH: 40.0' CAVED DEPTH: Not Applicable DRY AUGER: Not Applicable WET ROTARY: 0' to 40' BACKFILL: Cement-Bentonite Grout LOGGER: R. Fasone DRILL RIG: ABDU-38 HAMMER TYPE: Manual																
AL) 2016 (Ī	U	5	50	Bayou De Cade Marsh Creation a Restoration	ind Ri	dge			LC	OG (OF E	BOR	INC	3 N	O. E	3-0	5
OG (FIN			\equiv		(TE-0138, Task 1)													
FCBR_L(Terrebonne Parish, Louisiana Project No. 04.5									.551	740	66	F	LA.	TE	A-2	<u>'</u> 1	

	Τ.				LOCATION, One Plate 4			CLA	ASSIF	ICAT	ION			SHE	AR S	TREN	GTH	
ОЕРТН, FT	WATER LEVEL	SYMBOL	MINITES	BLOWS PER FOOT	LOCATION: See Plate 1 COORDINATES: N 29° 22' 57.4" W 90° 54' 46.95" SURFACE EL.: -6.1'	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	□Pe	netrom rvane and Var	neter	Ur	nconfine Triax ure Va	ial 🔴
	WAT	0	à	BLO		S H	TINO	PASS 200 S	CON	==	PL/	PLAS		KI	IPS PE	R SQ F	т	
	Ĺ				STRATUM DESCRIPTION LEAN CLAY (CL), very soft to soft, gray		_						0	.5 1	.0 1	.5 2.	0 2.	5
<u> </u>					- with an organic clay layer at 8"		-		36	42	23	19 -	▲◇					
-	-						-		47			-	<∞					
- 5 -					- with silt pockets and roots at 4'		- 88		35			_	◇●				•	
			M		- firm from 6.5' to 10'		-			44	47	-						
-	$\frac{1}{1}$		Λ	N=8	- with silt pockets at 8'		-			41	17	24 -		_				
—10 —	1				·		- 81 -		43			_	1 4					
							-		40			-	4					
-							-		66	47	18	29 -	▲ ◊					
—15 —					- with silt pockets at 14'		- 63		66			_	▲● <	>				
<u> </u>					- with siltstone and roots at 16'		-		52			-		>				
Ŀ					- firm, with silt pockets below 18'		_		62	36	19	17 -	}					
-20 -							_		02	30	19	17 - –] `					
							-					-						
<u> </u>					ORGANIC CLAY (OH), firm, dark gray	23.0			111				→	•				
-25 -	-						_		' ' '			_	ľ					
							-					-						
					- with a clay layer at 28'		_		31	216	49	- 167 -						
-30 -	-				- with an organic layer at 29.5'		-			210	75	-		_				
ļ							-					-						
					SILT (ML), gray, with clay pockets and laminations	33.0			38				▲ ◇					
-35 -	1						-					_						
							-					-						
/07/18					FAT CLAY (CH), firm, gray, with silt - with silt laminations at 38'	38.0	- 73		52			-	\ \dag{a}					
⁸ –40 –	1				- with siit iaminations at 38		_					_						
610.G							-					-						
TE 042							-		53			-	\	•				
MPLAT MPLAT									Т	COM	PLET	ION D	L ATE:	Marc	h 30,	, 2018	 }	
NOT ≥		_	s ar	nd symb	ols defined on Plates A-32a and A-32b.					TOTA	AL DE	PTH:	60.0'					
O DA									- 1			PTH: ER: No						
FUGR										WET	ROTA	ARY:	0' to 6	0'				
.GPJ									- 1			Cem R. Fa		enton	ite G	rout		
74066										DRIL	L RIG	: ABC	U-38					
04.551										HAMI	MER	TYPE:	Man	ual				
BR_LOG (FINAL) 2016 04.55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18 BR_LOG (FINAL) 2016 04.55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18	ħ	JG	R	20	Bayou De Cade Marsh Creation a Restoration	nd Ri	dge		'	LC)G (OF E	BOR	RINC	3 N	O. I	3-06	6
OG (FIN.			$\widehat{}$		(TE-0138, Task 1)													
BR_LC		- 9	\wedge		Terrebonne Parish, Louisiana			Proj	ect No). 04	<u> </u>	740	66	Ы	ΔΤ	- Δ	-22	<u> </u>

PLATE A-22a

04.55174066

Terrebonne Parish, Louisiana

					LOCATION: See Plate 1			CLA	ASSIF	ICAT	ION			SHE	AR S	TREN	GTH	
DEPTH, FT	WATER EVE	SYMBOL	SAMPLES	BLOWS PER FOOT	COORDINATES: N 29° 22' 57.4" W 90° 54' 46.95" SURFACE EL.: -6.1' STRATUM DESCRIPTION	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID		PLASTICITY INDEX (PI)	□Pe ◇To △Ha	netron rvane and Va	neter ne IPS PE	Un Miniati R SQ F	confined Triaxial Ire Vane	•
	+		\mathbf{M}	N=2	FAT CLAY (CH), firm, gray, with silt - soft at 45'								0	.5 1	.0 1	.5 2.0	2.5	_
- - - - -50 -	- - - - -			11-2	- soft at 45' - soft to firm, with silt pockets at 48'		- - - 61 -		67			- - - - -	<	•				
- - 55 - - -	- - - - -				- with shells below 58'		- - - -			98	30	- 68 - - - -		> 4				
- 60 -	1					- 60.0	<u> </u>	<u> </u>	52 — —		L	<u> </u>			L	-	_	_
- - - - - - - - - - - - - - - - - - -																		
			Ш							0014	DI ET	1011 5	<u> </u>			0040		_
FCBR_LOG (FINAL) 2016 04:55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18			ns ai	nd symb	ols defined on Plates A-32a and A-32b.	CAVED DEPTH: Not Applicable DRY AUGER: Not Applicable WET ROTARY: 0' to 60' BACKFILL: Cement-Bentonite Grout LOGGER: R. Fasone DRILL RIG: ABDU-38 HAMMER TYPE: Manual												
NAL) 2016	F	U G		20	Bayou De Cade Marsh Creation a Restoration	nd Ri	dge			LC	OG (OF E	BOR	RINC	3 N	O. E	3-06	
0G (FI.	V				(TE-0138, Task 1)													
-CBR_L			\sim		Terrebonne Parish, Louisiana	Terrebonne Parish, Louisiana Project No. 04.55174066 PLATE A-22										-22b)	

	LOCATION: See Plate 1			CLA	ASSIF	ICAT	ION			SHE	AR ST	renc	HT
DEPTH, FT WATER LEVEL SYMBOL SAMPLES BLOWS PER FOOT	COORDINATES: N 29° 22' 56.36" W 90° 55' 00.18"	STRATUM DEPTH, FT	WT,	0.% O.%	%.		0	È€		netrom	neter		onfined ▼ Triaxial ●
DEPTH, FT ATER LEVI SYMBOL SAMPLES SAMPLES FOOT	SURFACE EL.: -1.0'	STRA	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC	PLASTICITY INDEX (PI)		and Var	ne		re Vane 🛦
MAN NO BE	STRATUM DESCRIPTION	000	5	PAS 200	> ō	_	Δ.	∃ ≥	,			R SQ FT 5 2.0	
	FAT CLAY (CH), very soft, gray, with silt pockets - with a 4" organic clay layer with peat at 0'		- 66		59			_	•••	.0		2.0	1.0
	- with organics from 0.25' to 12' - firm from 2' to 12'		-		45			-		▲ >			
-5-			-		42	63	20	43-		A			
			-		38			-		• ♦			
			- - 91		32			-		• •			
_10 _					41	41	20	21 -		△			
	- soft at 12'		_		45	-	20	-					
	- firm of 14'		[_					
-15 -	- soft below 16'		F.,		34			_	*	A			
			- 90 -		35			-					
-20			_		50			_	A				
			-					-					
	LEAN CLAY (CL) , soft to firm, gray, with some sand pockets	23.0	-			43	21	22 -		>			
-25	cana position		-					-					
	FATOLAY (OLD and asset	28.0	-					-					
-30	FAT CLAY (CH), soft, gray - with organics at 28'		- 56		74			- -	•<				
			-					-					
	- with silt and sand seams at 33'		-					-					
-35-			_					_					
_∞		- 38.0	_					-					
1/20/90	SILT (ML), gray, with sand pockets and clay seams		-	92	31			_					
100.		40.0	F					-					
042610			-					-					
PLATE						COM	DI ET	ION D	∆TE∙	More	h 30	2019	
NOTES: 1. Terms and symbol	ols defined on Plates A-32a and A-32b.					TOTA	AL DE	PTH:	40.0'			2010	
NO DAT								EPTH: ER: No					
FUGE								ARY:			ite Gr	out	
96.GPJ						LOG	GER:	R. Fa	sone		iile Oi	out	
551740								: ABC TYPE:					
NOTES: 1. Terms and symbol 1. Terms are symbol 1. Terms and symbol 1. Terms and symbol 1. Terms are symbol 1. Terms and symbol 1. Terms are symbol 1. Terms and symbol 1. Terms are symbo	Bayou De Cade Marsh Creation an Restoration	nd Ri	dge			LC	OG (OF E	BOR	RINC	3 NO	Э. В	-07
3 (FINAL	(TE-0138, Task 1)												
CBR_LOC	Terrebonne Parish, Louisiana			Proj	ect No		.551	740	66	F	PLA	TE A	A-23

						LOCATION: See Plate 1			CL	ASSIF	ICAT	ION			SHE	AR S	TREN	GTH	
ЭЕРТН, FT	ATED LEVE	WATER LEVEL SYMBOL	SAMPLES	970 9/00	FOOT	COORDINATES: N 29° 22' 17.61" W 90° 55' 11.02" SURFACE EL.: -2.0'	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦To	enetron rvane and Va	ne	Miniat	confine Triaxi ure Var	al 🌑
	1	⋛		٥	۵	STRATUM DESCRIPTION		3	PA 200	3		_	곱 ≤	١ ,			R SQ F		5
	Ť	1				SANDY SILT (ML), gray, with clay layers		_	59	12			_		.5	.0 1	.5 2.	2.0	
-	-					- with organics at 0'		- -	33	27	23	21	2 -	•					
- 5 -				N	=22	SILTY SAND (SM), medium-dense, gray, with clay pockets	+ 4.0		29	31			_						
-	+			-N	=20	FAT CLAY (CH), soft to firm, gray	6.8	-		-			-						
- - 10 -						- with a 3-inch layer of silt at 8'		-		45	56	19	37 -		•				
-						- with a 2-inch sand layer and shells at 10'	12.0	- 86		38			_	•					
-	-					LEAN CLAY (CL), firm, gray - with trace sand pockets at 12' - soft at 14'		- -		38			-	*					
─15 - -	7					- very soft below 16'		-		35	43	20	23 -	◇▲					
-						FAT CLAY (CH), soft, gray, with organics	18.0	- - 80		38 43				A					
—20 - -	-					- with a 1" silt layer at 18"		_ 00 -		43			-	-	Ĭ				
-	-							- -			80	26	54 -		\$				
25 - -								- - -					- - -						
- - -30 -								- - 60		73			- - -	•		*			
-	-							- -					-						
- 35 - - -	_					- with a 6-inch peat layer at 33' - with a 4-inch silt layer at 35.5'		- - -					- - -	*					
06/07/18	-					SILT (ML), gray - with a 3-inch peat and organic layer at 38'	38.0	-			23	21	2 -						
42610.GDT (- 40.0	- - -					- - -						
FCBR_LOG (FINAL) 2016 04-55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06.07/18			ms a	and	symb	ools defined on Plates A-32a and A-32b.		-			TOTA CAVE DRY WET BACK LOGG DRIL	AL DE ED DE AUGE ROTA KFILL GER: L RIG	ION D. PTH: EPTH: ER: No ARY: (: Cem R. Fa: : ABD TYPE:	40.0' Not Apport Apport to 4 ent-B sone	Applicab blicab 10' entor	able le			
AL) 2016	Ī	Ù (5	2	0	Bayou De Cade Marsh Creation a Restoration	and Ri	dge			LC	OG (OF E	BOR	RINC	G N	O. I	3-08	}
NE (FIN	V					(TE-0138, Task 1)			D	oot NI									
FCBR			_/	`		Terrebonne Parish, Louisiana			Proj	ect No		.551	740	66	F	PLA	TE	A-2	4

	T.				LOCATION: See Plate 1			CL	ASSIF	ICAT	ION			SHE	AR S	TREN	GTH	
DEPTH, FT	11, 11 C T T A A A A	WAIEK LEVEI SYMBOI	SAMPLES	BLOWS PER FOOT	COORDINATES: N 29° 21' 56.94" W 90° 55' 47.05" SURFACE EL.: -1.4' STRATUM DESCRIPTION	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦To	enetron irvane and Vai K	ne		confine Triaxia ure Van	al 🌑
	+	1			-PEAT (PT), gray	0.5							0	.5 1	.0 1	.5 2.	2.5	
-	1				FAT CLAY (CH), very soft, gray, with organics	2.0			44	82	24	58 -	4					
- - - 5 - -	-			N=2/12" N=Push	SILTY SAND (SM), very loose, gray, with clay pockets		- - - -	33	20 14			- - - -	-					
-	-			N=9	LEAN CLAY (CL), firm, gray	8.0	-			47	22	25 -						
—10 — -	1				- very soft at 10'		- -		31	46	21	25 -	A >					
-					- soft below 12'	14.0	- - 88		39			-	◇4					
—15 —					FAT CLAY (CH), firm, gray	14.0	_		49			-		♦▲				
-					51.1.40		-		53	62	24	38 -	*	•				
- 20 -					- soft below 18'		- 75 - -		48			- - -	*•					
- - 25 - - -	-						- - 65 - -		60			- - - -	•					
- 30 - -	-				- with a 4" peat layer at 29.5'		- - - -					- - - -	*					
- - -35 - -	-				- with a 1" peat layer at 33'		- - 91 - -		35			- - - -	◇ •					
06/07/18	-				SANDY LEAN CLAY (CL), soft, gray, with silt seams	38.0	-					-	·					
						- 40.0	- - - -					 - - -	-					
FCBR_LOG (FINAL) 2016 04:55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18			rms a	and symb	ols defined on Plates A-32a and A-32b.	ı		1		TOTA CAVE DRY . WET BACK LOGG DRILI	AL DE ED DE AUGE ROT/ (FILL: GER: L RIG	ION D PTH: EPTH: ER: N ARY: Cem R. Fa : ABE TYPE:	40.0' Not Apport	Applic olicab 40' sentor	able le			
AL) 2016	ħ	Ü	Ç.	50	Bayou De Cade Marsh Creation a Restoration	nd Ri	dge			LC)G (OF E	BOF	RINC	3 N	O. E	3-09	
OG (FIN.	V		3		(TE-0138, Task 1)			T_										
FCBR_L					Terrebonne Parish, Louisiana			Proj	ect No		.551	740	66	F	LA.	TE	A-2	5

		6.4	LOCATION: See Plate 1			CL	ASSIF	ICAT	ION			SHE	AR S	TREN	ЭТН	
ОЕРТН, FT	SYMBOL SAMPI ES	BLOWS PER FOOT	COORDINATES: N 29° 23' 01.59" W 90° 53' 33.96" SURFACE EL.: -4.3'	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦To	netron rvane and Va	ne	Miniatu		ial 🌑
	$ \hat{\mathbf{x}} $	<u> </u>	STRATUM DESCRIPTION	_	3	PA 20	8			_ =	0			R SQ F		5
			LEAN CLAY WITH SAND (CL), very soft, gray				31				<u> </u>	.5 1		1 1	, 2	_
			SILTY SAND (SM), gray, with clay pockets	2.0	-	50	28									
- -5-		N=7	- loose below 4'		-					_						
		N=5	SANDY SILT (ML), loose, gray, with clay pockets	6.0	-		61	25	24	1 -						
-10 -			FAT CLAY (CH), soft, gray, with wood and organics	9.0	- -		111	81	27	54 -	◇ ▲					
			SILTY SAND (SM), gray, with clay pockets and shells	12.3	-		30			-						
- 15 -			FAT CLAY (CH), soft, dark gray, with sand seams		ŀ		113			_	△					
				16.0							:			†		
	1				-					-						
—20 —]				-					_						
-	-				-					-						
]				-					-						
—25 —					-					_						
<u> </u>]				Ŀ					-						
F .	1									_						
-30 -	1				-					_						
ŧ.]				Ŀ					-						
ļ					ŀ					-						
—35 —					-					_						
	-				-					-						
- - - -40 -					F					_						
-40 -	1				-					_						
	-				-					-						
]				F					-						
NOT		and symb	Dools defined on Plates A-32a and A-32b.	1		ı		TOTA CAVE DRY WET BACK LOGG DRIL	AL DE ED DE AUGE ROTA (FILL: GER: L RIG	ION DAPTH: EPTH: ER: Not ARY: (Cemer R. Fast ABD TYPE:	16.0' Not Apport Apport to 1 ent-Bosone U-38	Applicab 6' entor	able le			
7	Tu G	RO	Bayou De Cade Marsh Creation a Restoration	nd Ri	dge			LC)G (OF E	BOR	RINC	3 N	O. E	3-10)
		$\stackrel{\sim}{\approx}$	(TE-0138, Task 1)													
		\sim	Terrebonne Parish. Louisiana			Proj	ect No). 04	5 5 1	740	66		οι Δ΄	TF	Δ_2	6

PLATE A-26

04.55174066

Terrebonne Parish, Louisiana

FCBR_LOG (FINAL) 2016 04.55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18


		_				LOCATION: See Plate 1			CLA	ASSIF	ICAT	ION			SHE	AR S	TREN	GTH	
DEPTH, FT	,	WATER LEVE	SYMBOL	SAIVIL LES	BLOWS PER FOOT	COORDINATES: N 29° 23' 06.77" W 90° 53' 10.61" SURFACE EL.: -4.6'	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦To	enetron rvane and Va K	ne	Un Miniati R SQ F		al 🌑
		_												0	.5 1	.0 1	.5 2.	2.5	5
FCBR_LOG (FINAL) 2016 04.35174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18 FCBR_LOG (FINAL) 2016 04.35174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18		<u>S:</u>	erms			STRATUM DESCRIPTION FAT CLAY (CH), very soft to soft, gray - with shells from 0' to 0.5' - with wood from 0.5' to 1.2' - with sand from 1.2' to 1.8' - with peat at 4' - with sand traces at 6' - with sand seams at 12' pols defined on Plates A-32a and A-32b.	- 16.0		83	86 26 85 64 74 63 62 61	TOTA CAVE DRY	L DE ED DE AUGE	36	ATE: 16.0' Not App	Aprilicablicab	2, 20 able	5 2.		
04.55174066.GPJ FUGI											WET BACK LOGO DRILI	ROTA (FILL: GER: L RIG	ARY: (Cem R. Fa : ABC TYPE:	0' to 1 ent-B sone OU-38	6' entor		rout		
VAL) 2016	I	u	G	R	20	Bayou De Cade Marsh Creation a Restoration	nd Ri	dge			LC)G (OF E	BOF	RING	3 N	O. E	3-11	I
LOG (FIN	V			$\widehat{\widehat{\wedge}}$		(TE-0138, Task 1)			Proi	ect No).								
FCBR						Terrebonne Parish, Louisiana						551	740	66	F	PLA	TE	A-2	7

	T				LOCATION: See Plate 1			CL	ASSIF	ICAT	ION			SHE	AR S	TREN	GTH	
DEPTH, FT		WAIER LEVEL	SAMPLES	BLOWS PER FOOT	COORDINATES: N 29° 23' 24.77" W 90° 53' 10.51" SURFACE EL.: -6.6' STRATUM DESCRIPTION	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦ To		ne IPS PE	Miniat	т	ial ● ne ▲
	+				FAT CLAY (CH), very soft, dark gray									0.5 1	1.0 1	.5 2.	0 2.	5
	1				- with some shells at 0'		-		82									
	+				- gray below 2'		-		35	61	23	38	•					
- 5 -	7						_		32			_	•	\				
-	1			N=6	SILTY SAND (SM), loose, gray, with clay and wood	6.0		35	30									
-	$\frac{1}{2}$				FAT CLAY (CH), gray	8.0												
- 10	1	1			SANDY SILT (ML), medium-dense, gray, with clay pockets and peat layers	9.0			28			_						
-	+		. <u>- </u> X	N=13	pockets and peat layers		-	53	32									
	7			N=8	FAT CLAY (CH), firm to stiff, gray, with wood and	12.5	-											
- 15	1	71	<u> </u>		organics PEAT (PT), very soft to soft, black, with clay seams	14.0	_		386					4				
	$\frac{1}{2}$	1/2	11/		and an organic odor	16.0	-	 					 	-	<u> </u>	+	+	
	7						-]					
- 20	1						-					-						
	+						-						1					
	1						-											
- 25	$\frac{1}{2}$						_											
—25 —	7						F					-						
- :	1						-											
-	$\frac{1}{2}$						-						1					
—30 —	1						-					-						
-	1						-											
	-						-						1					
- 35 -	1						-					-	1					
	+						-						1					
5/07/1	7						-						1					
—40 —	1						_					-	1					
610.G	$\frac{1}{2}$						-											
E 042	1						 											
MPLAT					I	1	<u> </u>		\Box	COM	PLFT	ION D	ATF:	Apri	1 2. 20) 18		
NOT			ms a	and sym	abols defined on Plates A-32a and A-32b.					TOTA	AL DE	PTH:	16.0'			-		
DAI				•								PTH: ER: N						
UGK												=R. N ARY:			viC			
a Cae												Cem			nite G	rout		
4066.0									- 1			R. Fa						
1.5517.												TYPE:						
FCBR_LOG (FINAL) 2016 04:55174066:GPJ FUGRO DATA TEMPLATE 042510.GDT 06/07/18	F		-	20	Bayou De Cade Marsh Creation a Restoration	nd Ri	dge			LC	OG (OF E	BOF	RIN	G N	O. I	3-12	2
G (FINAL			3		(TE-0138, Task 1)													
LCBK_LC					Terrebonne Parish, Louisiana			Proj	ect No		.551	740	66	F	PLA	TE	A-2	28

				LOCATION: See Plate 1			CL	ASSIF	ICAT	ION			SHE	AR ST	ΓREN	GTH .
DEPTH, FT	WATER LEVEI	SYMBOL	BLOWS PER FOOT	COORDINATES: N 29° 23' 17.88" W 90° 52' 54.71" SURFACE EL.: -5.1'	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦To	netrom rvane ind Var Kl	ne		confined Triaxial Ire Vane
				STRATUM DESCRIPTION								0.	.5 1	.0 1.	5 2.0	2.5
	-	· . -		SILT WITH SAND (ML), stiff, gray, with clay lenses and organics		-	84	25			-	1		_		
			N=9	SILTY SAND (SM), loose, gray	2.0	-					-					
- 5 - 			N=4	LEAN CLAY (CL), very soft to soft, gray - with peat layers and sand layers at 5.5'	+ 4.5	-	52	28			-	◇ ▲				
	- <u> </u> -	<u>///</u>		SHELLS	8.0											
		- <u>-</u> -		LEAN CLAY (CL), soft, gray, with organics	+ 9.0 + 10.0			40				♦▲				
-10 - 				ORGANIC CLAY (OH), soft, gray	T 10.0	-		82	123	38	85 -	4				
				- with wood below 12' PEAT (PT), very soft to soft, black and brown, with	14.0	-		162			-	•				
─15 <i>-</i>	 	<u>, \/,</u>		clay layers, rootlets, and an organic odor	- 16.0	<u> </u> 		206			-	- 			+	-+-
 -20 - 						- - - - -					- - - - -	-				
25 30	-					- - - - -					- - - -	-				
	- - - - - - -					- - - - - -					- - - - -					
E 042610.GDT 06						- - - -					- - - -	-				
04.55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18		erms a	and syn	nbols defined on Plates A-32a and A-32b.	1				TOTA CAVE DRY WET BACK LOGG DRIL	AL DE ED DE AUGE ROTA (FILL: GER: L RIG	ION D PTH: EPTH: ER: N ARY: Cem R. Fa C: ABD TYPE:	16.0' Not Apport Apport to 1 apport to 200-38	Applic blicabl 6' enton	able le		
AL) 2016 0	Fu	G	20	Bayou De Cade Marsh Creation a Restoration	nd R	idge			LC	OG (OF E	BOR	INC	3 NO). E	3-13
FCBR_LOG (FINAL) 2016				(TE-0138, Task 1)												
FCBR_L		_/		Terrebonne Parish, Louisiana			Proj	ect No		.551	740	66	F	PLA ⁻	TE .	A-29

		.1 1	T		LOCATIONI: Con Ploto 1			CLA	ASSIF	ICAT	ION			SHE	AR S	TREN	GTH	
DEPTH, FT	MATED I EVE	SYMBOL	SAMPLES	BLOWS PER FOOT	LOCATION: See Plate 1 COORDINATES: N 29° 23' 37.93" W 90° 52' 43.31" SURFACE EL.: -4.8'	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦To	enetron Irvane and Vai	neter	Un	confine Triax ure Va	ial 🗨
	>	>	$\setminus \mid$	"	STRATUM DESCRIPTION		5	20 P.	ŏ				0			R SQ F .5 2.		5
-	-		1		FAT CLAY (CH), very soft, gray - with shells and roots at 0'		-		48				- ▲◇					
-	1		1		- with shells and roots at o				86	79	26	53 -						
-	7		1						00	19	20		-					
— 5 - -	1						-	99	53			-						
-	+		χı	N=Push	- with a sand seam at 7'		-					-	$\frac{1}{2}$					
-	1				- with a 0.5" silt seam and shells at 8'		-		93									
—10 - _	1						_		144			-						
-	$\frac{1}{2}$		1		ORGANIC CLAY (OH), very soft, dark gray	12.0							<u> </u>					
-	1		-				-		185	165	47	118						
 15	1	屋			- with wood and peat below 14'	16.0	-		170			-	A					
-]					16.0												
-	1						-						1					
-20 -	+						-					-	1					
-	7						-						}					
-	1						-											
— 25 -	+						-					-	$\left\{ \right.$					
-	1						-						1					
-	1						-						1					
-30 -	-						F					_	1					
-	1						-					-						
-	1						_						}					
 35 -	4						L					_	}					
-	1						-						1					
	+						-					-	1					
0/90 ─40 -	1						_					_	1					
0.GD	1												}					
7	+						-						-					
- ATE	1								<u> </u>			-	1					
NO.												ION D PTH:		Marc	:h 28,	2018		
DATA	1.	Term	ns ar	nd symbo	ols defined on Plates A-32a and A-32b.							PTH:		Applic	able			
3RO [ER: N			le			
J FU									- 1			ARY: : Cem			ite G	rout		
36.GP										LOG	GER:	R. Fa	sone					
51740(: ABC						
04.5										. i⁄~iVII	VILIX	E.	ivial	iudi				
AL) 2016	F	U G	IR	20	Bayou De Cade Marsh Creation a Restoration	nd Ri	dge			LC	OG (OF E	3OF	RINC	3 N	O. E	3-14	4
FCBR_LOG (FINAL) 2016 04.55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18	V		<i>*************************************</i>		(TE-0138, Task 1)			1-										
FCBR_L			\mathcal{L}		Terrebonne Parish, Louisiana			Proj	ect No		.551	740	66	F	LA.	TE	A-3	0

					LOCATION: See Plate 1			CL/	ASSIF	ICAT	ION			SHE	AR S	TREN	GTH
DEPTH, FT	ייין ו מידראא	SYMBOL	SAMPLES	BLOWS PER FOOT	COORDINATES: N 29° 23' 11.23" W 90° 52' 43.43" SURFACE EL.: -8.1'	STRATUM DEPTH, FT	UNIT DRY WT, PCF	PASSING NO. 200 SIEVE, %	WATER CONTENT, %	LIQUID	PLASTIC LIMIT	PLASTICITY INDEX (PI)	♦To	enetron orvane and Va K	ne		confined ▼ Triaxial ● ure Vane ▲
					STRATUM DESCRIPTION								0	.5 1	.0 1	.5 2.0	2.5
F	+		7		FAT CLAY (CH), very soft, gray, with silt layers and shells		-		71			-	A				
Ė					- with gravel and roots at 2'		-	93	40			-	•				
- 5 ·	4			N=4	- with a 4" silty sand layer at 4.5'		_					-					
-	1				- with ferrous nodules below 6'		_		103			-	4				
+	-				FAT CLAY WITH SAND (CH), soft, gray	8.0	_	79	36			-	◇▲				
─10 · -	7		7		FAT CLAY (CH), very soft, gray	10.0	_		102			-	•				
<u> </u>	-		1				-		71	87	28	59 -	A				
- 15	_						-					_					
-	-						-		64			-	A				
-	1					18.0							† –		 	+	-+
—20 · -	1						_					-					
-	1						_					-					
-	-						-					-					
-25 ·	-						_					-					
-	7						-					-					
- -30	1						_					-					
-	1						-					-					
-	-						-					-					
—35 · -	1						-					-					
- <u>8</u> _	1						_					-					
./20/90	+						-					-					
-40 -	-											-					
7 1	1						-					-					
LATE.							_			06: 1		-					
MO.			ac -	nd erest	ole defined on Dietoe A 205 and A 205							ION D PTH:		Mar	ch 28,	2018	
DATA	Τ.	ıern	ıs a	na symb	ols defined on Plates A-32a and A-32b.					CAVE	D DE	PTH:	Not A				
GRO												ER: No ARY: (le		
J. FU									- 1			Cem			nite G	rout	
)66.GF												R. Fa					
4.55174(: ABC TYPE:					
FCBR_LOG (FINAL) 2016 04.55174066.GPJ FUGRO DATA TEMPLATE 042610.GDT 06/07/18	fi	Ų r		20	Bayou De Cade Marsh Creation a Restoration	nd Ri	dge			LC)G (OF E	BOF	RING	G N	O. E	3-15
OG (FINA.	V				(TE-0138, Task 1)												
FCBR_L(\sim		Terrebonne Parish, Louisiana			Proj	ect No		.551	740	66	F	PLA	TE	A-31



PLASTICITY CHART

2.00

Coarse Medium

0.425

0.075

0.005

(mm)

Coarse


19.0

75.0

152

Fine

4.75



SOIL STRUCTURE

Slickensided ·····	Having planes of weakness that appear slick and glossy.
Fissured ·····	Containing shrinkage or relief cracks, often filled with fine sand or silt; usually more or less vertical.
Pocket ·····	Inclusion of material of different texture that is smaller than the diameter of the sample.
Parting ·····	Inclusion less than 1/8 inch thick extending through the sample.
Seam	Inclusion 1/8 inch to 3 inches thick extending through the sample.
Layer	Inclusion greater than 3 inches thick extending through the sample.
Laminated ·····	Soil sample composed of alternating partings or seams of different soil type.
Interlayered ·····	Soil sample composed of alternating layers of different soil type.
Intermixed ·····	Soil sample composed of pockets of different soil type and layered or laminated structure is not evident.
Calcareous ·····	Having appreciable quantities of carbonate.
Carbonate	Having more than 50% carbonate content.



TERMS AND SYMBOLS USED ON BORING LOGS

SOIL CLASSIFICATION (1 of 2)

Project No.	
04.55174066	PL/

PLATE A-32a

STANDARD PENETRATION TEST (SPT)

A 2-in.-OD, 1-3/8-ID split spoon sampler is driven 1.5 ft into undisturbed soil with a 140-pound hammer free falling 30 in. After the sampler is seated 6 in. into undisturbed soil, the number of blows required to drive the sampler the last 12 in. is the Standard Penetration Resistance or "N" value, which is recorded as blows per foot as described below.

SPLIT-BARREL SAMPLER DRIVING RECORD

Blows Per Foot	Description
25 ·····	25 blows drove sampler 12 inches, after initial 6 inches of seating.
50/7" · · · · · · · · · · · · · · · · · · ·	50 blows drove sampler 7 inches, after initial 6 inches of seating.
Ref/3" · · · · · · · · · · · · · · · · · · ·	50 blows drove sampler 3 inches during initial 6-inch seating interval.

NOTE: To avoid damage to sampling tools, driving is limited to 50 blows during or after seating interval.

DENSITY OF GRANULAR SOILS

STRENGTH OF COHESIVE SOILS

Descriptive Term	*Relative Density, %	**Blows Per Foot (SPT)	Term	Undrained Shear Strength, ksf	Blows Per Foot (SPT) (approximate)
Very Loose ······	15	0 to 4	Very Soft ·····	······< 0.25 ······	·····0 to 2
Loose ······	15 to 35	·····5 to 10	Soft	······ 0.25 to 0.50 ······	·····2 to 4
Medium Dense ···	······35 to 65 ·····	·····-11 to 30	Firm · · · · · · ·	0.50 to 1.00	·····4 to 8
Dense ·····	·····65 to 85 ·····	·····-31 to 50	Stiff ·····	······ 1.00 to 2.00 ······	····· 8 to 16
Very Dense ······	85	·····> 50	Very Stiff ····	2.00 to 4.00	·····16 to 32
*Estimated from	n sampler driving reco	ord.	Hard ······	·····> 4.00 ·····	·····> 32

^{**}Requires correction for depth, groundwater level, and grain size.

SHEAR STRENGTH TEST METHOD

U = Unconfined Q = Unconsolidated - Undrained Triaxial

P = Pocket Penetrometer T = Torvane V = Miniature Vane F = Hand Vane

HAND PENETROMETER CORRECTION

Our experience has shown that the hand penetrometer generally overestimates the in-situ undrained shear strength of over consolidated Pleistocene Gulf Coast clays. These strengths are partially controlled by the presence of macroscopic soil defects such as slickensides, which generally do not influence smaller scale tests like the hand penetrometer. Based on our experience, we have adjusted these field estimates of the undrained shear strength of natural, overconsolidated Pleistocene Gulf Coast soils by multiplying the measured penetrometer reading by a factor of 0.6. These adjusted strength estimates are recorded in the "Shear Strength" column on the boring logs. Except as described in the text, we have not adjusted estimates of the undrained shear strength for projects located outside of the Pleistocene Gulf Coast formations.

Information on each boring log is a compilation of subsurface conditions and soil or rock classifications obtained from the field as well as from laboratory testing of samples. Strata have been interpreted by commonly accepted procedures. The stratum lines on the logs may be transitional and approximate in nature. Water level measurements refer only to those observed at the time and places indicated, and can vary with time, geologic condition, or construction activity.



TERMS AND SYMBOLS USED ON BORING LOGS

SOIL CLASSIFICATION (2 of 2)

Project No. 04.55174066

PLATE A-32b



APPENDIX B LABORATORY TESTING

					lde	entificati	on Tests				Field Sho Strength Es		Miniature Vane Tests	(Compressi	on Tests		
Sample No.	Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1a	1.0-2.0	37	22	15	30						0.50	0.20	0.38					
2	2.0-3.0				33					74		0.20	0.22					
3	4.0-6.0	35	19	16	28						1.00	0.30	0.82					
4	6.0-8.0				23						0.50	0.20	0.92					
5	8.0-9.5				21													
6	10.0-11.5				24													
7	12.0-14.0				26						0.25	0.15	0.13					
9	16.0-17.5	43	21	22	27													
10	18.0-20.0				44	79	113					0.20	0.25	UU	5	0.26	Α	
11	23.0-25.0	126	34	92	116			2.472			0.25	0.23	0.68					С
12	28.0-30.0	473	321	152	321						1.25	0.53	2.58					
13	33.0-35.0				41	80	114				0.25	0.20	0.29	UU	9	0.29	Α	
14	38.0-40.0				59	69	109				0.25	0.18	0.68	UU	11	0.45	Α	
15	43.0-45.0				57						0.25	0.20	0.57					
16	48.0-50.0	82	27	55	59						0.25	0.20	0.53					
17	53.0-55.0				67	60	100				0.25	0.20	0.57	UU	15	0.45	С	
18	58.0-60.0	96	27	69	37						0.25	0.43	0.91					

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pHR = Resistivity CI = Chlorides



Bayou De Cade Marsh Creation and Ridge Restoration

SUMMARY OF TEST RESULTS - BORING B-01

(TE-0138, Task 1)

Project No.

PLATE B-1a

LELAP Lab ID #10001

Terrebonne Parish, Louisiana

04.55174066

					lde	entification	on Tests				Field She Strength Es	ear timate	Miniature Vane Tests	C	Compressi	on Tests		
Sample No.	Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1	0.0-2.0				67							0.05	0.08					
2	2.0-4.0	39	23	16	36							0.20	0.09					
3	4.0-6.0				28					60	0.50	0.10						
4	6.0-7.5				32													
5	8.5-10.0				34					33								
6	10.5-12.0				32													
7	12.0-14.0				44								0.26					
8	14.0-16.0	121	36	85	74							0.10	0.14					
9	16.0-18.0				76			2.689			0.25	0.18	0.57					С
10	18.0-20.0				67	59	99					0.18	0.34	UU	5	0.32	A,C	
	24.0-25.0	39	19	20	163						0.75	0.18	0.45					
12	28.0-30.0				29	75	97					0.40	0.40	UU	8	0.20	С	
13	33.0-35.0				34						0.25	0.28						
14	38.0-40.0				41					99	0.25	0.11	0.29					
15	43.0-45.0	34	20	14	48						0.25	0.20	0.55					
16	48.0-50.0				57	68	106				0.25	0.10	0.54	UU	13	0.40	Α	
17	53.0-55.0				66						0.25	0.15	0.59					
18	58.0-60.0	100	28	72	73						0.75	0.20	0.73					
						-	DE 05 T								D TEAT T			

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pHR = Resistivity CI = Chlorides



Bayou De Cade Marsh Creation and Ridge Restoration

SUMMARY OF TEST RESULTS - BORING B-02

(TE-0138, Task 1)

LELAP Lab ID #10001

Terrebonne Parish, Louisiana

Project No. 04.55174066

PLATE B-1b

					lde	entificati	on Tests				Field She Strength Es		Miniature Vane Tests	(Compressi	on Tests		
Sample No.	Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1	0.0-2.0				65							0.30	0.11					
2	2.0-4.0				31							0.30	0.19					С
4	6.0-7.5				11					19								
6	10.0-11.5				29					17								
7	12.0-14.0				39	86	120						0.57	UU	5	0.34	Α	
8	14.0-16.0	39	18	21	86								0.50					
9	16.0-18.0				81	54	98					0.20	1.12	UU	6	0.39	С	
10	18.0-20.0				65							0.25	0.40					
11	23.0-24.2								38.94									
	24.2-25.0				69	58	98		6.28			0.30		UU	9	0.30	Α	
12	28.0-30.0				28					87		0.10						
13	33.0-35.0				39					91		0.10						
14	38.0-40.0				53	71	108					0.10		UU	14	0.47	Α	
15	43.0-45.0											0.45						
16	48.0-50.0				60	69	110					0.15		UU	17	0.57	A,B	
17	53.0-55.0	83	26	57								0.15						
18	58.0-60.0				70	59	100					0.20		UU	21	0.59		
	4				•	·		-0-			T. (D.E.			O.T. I.E.	D TECT T	\ \(D=0\)		

-fugro

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane

C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pH

R = Resistivity CI = Chlorides



SUMMARY OF TEST RESULTS - BORING B-03

(TE-0138, Task 1)

Project No.

PLATE B-1c

LELAP Lab ID #10001

Terrebonne Parish, Louisiana

04.55174066

					lde	entificati	on Tests				Field She Strength Es	ear timate	Miniature Vane Tests	C	Compression	on Tests		
Sample No.	Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1	0.0-2.0	127	34	93	59							0.35	0.14					
2	2.0-4.0				54				3.70			0.40	0.14					
3	4.0-6.0	60	18	42	50			2.569				0.55	0.25					С
4	6.0-8.0				41	85	119					0.25	0.69	UU	3	0.38	Α	
5	8.0-10.0				52							0.15	0.25					
6	10.0-12.0				34							0.10	0.20					
7	12.0-14.0				33	87	116					0.10	0.14	UU	5	0.25	Α	
8	14.0-16.0				35							0.10	0.18					
9	16.0-18.0				37							0.10	0.27					
10	18.0-20.0				34							0.10	0.26					
11	23.0-25.0				38	84	117				0.50	0.20		UU	9	0.22	Α	
12	28.0-29.5	30	20	10								0.10						
13	33.0-35.0				45	79	115				0.75			UU	12	0.34	С	
14	48.0-50.0	46	20	26														
				•	•	•	DE 05 T		•	•					D TEOT T		•	•

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pH

R = Resistivity CI = Chlorides



SUMMARY OF TEST RESULTS - BORING B-04

(TE-0138, Task 1)

Terrebonne Parish, Louisiana

Project No.

PLATE B-1d 04.55174066

LELAP Lab ID #10001



					lde	entificati	on Tests				Field She Strength Es	ear timate	Miniature Vane Tests	C	Compression	on Tests		
Sample No.	Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1	0.0-2.0	55	18	37	60							0.10	0.14					
2	2.0-4.0				52	71	108					0.20	0.73	UU	3	0.39	Α	
3	4.0-6.0	65	20	45	45			2.606				0.30	0.72					С
4	6.0-8.0				32							0.15	0.47					
5	8.0-10.0				33	87	117					0.25	0.52	UU	3	0.70	Α	
6	10.0-12.0				37					95		0.20	0.12					
7	12.5-14.0	36	20	16	46													
8	14.0-16.0				52	72	110					0.15	0.44	UU	5	0.35	Α	
9	16.0-18.0				35							0.10	0.40					
10	18.0-20.0	31	22	9	32													
11	23.0-25.0				33	89	118					0.10	0.29	UU	7	0.83	Α	
12	29.0-30.0				231							0.60	2.74					
13	33.0-35.0	32	19	13	36													
14	38.0-40.0				42							0.20	0.42					
						T\/		-от			T/0		II LIDE	OTUE	D TECT T	\/DE0		

-fugro

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane

C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pH

R = Resistivity CI = Chlorides



SUMMARY OF TEST RESULTS - BORING B-05

(TE-0138, Task 1)

LELAP Lab ID #10001

Terrebonne Parish, Louisiana

Project No. 04.55174066

PLATE B-1e

				lde	entificati	on Tests						Miniature Vane Tests	(Compressi	on Tests		
Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
0.0-2.0	42	23	19	36							0.15	0.14					
2.0-4.0				47			2.533				0.05	0.14					С
4.0-6.0				35	88	119					0.10	2.17	UU	3	0.33	Α	
6.5-8.0	41	17	24														
8.0-10.0				43	81	115						0.47	UU	3	0.60	С	
10.0-12.0				40							0.20	0.43					
12.0-14.0	47	18	29	66							0.20	0.14					
14.0-16.0				66	63	104					0.25	0.18	UU	5	0.30	Α	
16.0-18.0				52							0.25	0.21					
18.0-20.0	36	19	17	62							0.25	0.54					
23.0-25.0				111							0.20	0.58					
28.0-30.0	216	49	167	31								0.61					
33.0-35.0				38							0.15	0.18					
38.0-40.0				52	73	110					0.20	0.51	UU	11	0.54	С	
43.0-45.0				53							0.20	0.66					
48.0-50.0				67	61	101					0.20	0.72	UU	14	0.47	С	
53.0-55.0	98	30	68								0.25	0.99					
58.0-60.0				52							0.20	0.75					
	0.0-2.0 2.0-4.0 4.0-6.0 6.5-8.0 8.0-10.0 10.0-12.0 12.0-14.0 14.0-16.0 18.0-20.0 23.0-25.0 28.0-30.0 33.0-35.0 38.0-40.0 43.0-45.0 48.0-50.0 53.0-55.0	(%) 0.0-2.0	(%) (%) 0.0-2.0	(%) (%) (PI) 0.0-2.0	Depth (ft) Liquid Limit (%) Plastic Limit (%) Plasticity Index (PI) Moisture Content (%) 0.0-2.0 42 23 19 36 2.0-4.0 47 47 47 4.0-6.0 35 41 17 24 8.0-10.0 43 40 43 10.0-12.0 40 40 40 12.0-14.0 47 18 29 66 14.0-16.0 66 66 66 16.0-18.0 52 111 62 23.0-25.0 111 31 33 38.0-30.0 216 49 167 31 38.0-40.0 52 53 48.0-50.0 53 48.0-50.0 98 30 68 67	Depth (ft) Liquid (%) Plastic (%) Plastic limit (%) Moisture (PI) Dry Unit Weight (pcf) 0.0-2.0 42 23 19 36 2.0-4.0 47 47 4.0-6.0 35 88 6.5-8.0 41 17 24 8.0-10.0 43 81 10.0-12.0 40 40 12.0-14.0 47 18 29 66 14.0-16.0 66 63 16.0-18.0 52 111 28.0-20.0 36 19 17 62 23.0-25.0 111 28.0-30.0 216 49 167 31 33.0-35.0 38 38 38 38 48.0-50.0 52 73 48.0-50.0 667 61 53.0-55.0 98 30 68	(%) (%) (PI) (%) (pcf) (pcf) 0.0-2.0 42 23 19 36 36 36 36 36 36 36 36 36 36 36 36 36 36 36 36 36 37 35 88 119 35 88 119 35 88 119 35 88 119 115 36 36 38 115 36 36 36 37 36 37 36 37 36 36 36 36 36 36 36 36 36 37 36 36 37 36 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37	Depth (ft) Liquid (w) Plastic Limit (w) Plasticity Index (PI) Moisture Content (weight (pcf)) Dry Unit Weight (pcf) Total Unit Weight (pcf) Specific Gravity 2.0-4.0 42 23 19 36 2.533 4.0-6.0 35 88 119 6.5-8.0 41 17 24 35 8.0-10.0 43 81 115 10.0-12.0 40 115 115 12.0-14.0 47 18 29 66 3 104 16.0-18.0 52 31 31 33 35 38 30 38 38 30 38 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30	Depth (ft) Liquid Limit (%) Plastic limit (%) Plasticity Index (PI) Moisture Content (%) Dry Unit (pcf) Total Unit Weight (pcf) Specific Gravity Organic Content (%) 0.0-2.0 42 23 19 36 2.533 2.533 4.0-6.0 35 88 119 6.5-8.0 41 17 24 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 115 1	Depth (it)	Depth (it) Liquid (timit (%) Plastic Plasticity Index (Content (PI) (%) Plastic Plasticity Pl	Depth Liquid Plastic Plasticity Moisture Index (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (%) (Depth Liquid Control Control	Depth Liquid Plastic Plasticity Moisture Dry Unit Content Co	Depth Liquid Plastic Plasticty Moisture Dry Unit Total Unit Correct Correct	Pepth Liquid Plastic Plastic	Purply Plastic Plast

-fugro

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane

C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pH

R = Resistivity CI = Chlorides



SUMMARY OF TEST RESULTS - BORING B-06

(TE-0138, Task 1)

Project No.

PLATE B-1f

LELAP Lab ID #10001

Terrebonne Parish, Louisiana

04.55174066

					lde	entificati	on Tests				Field Sho Strength Es	ear timate	Miniature Vane Tests	C	Compressi	on Tests		
Sample No.	Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1	0.0-2.0				59	66	105					0.20	0.34	UU	3	0.22	Α	
2	2.0-4.0				45							0.35	0.64					
3	4.0-6.0	63	20	43	42							0.30	0.58					
4	6.0-8.0				38							0.40	0.51					
5	8.0-10.0				32	91	120					0.40	1.02	UU	3	0.69	Α	
6	10.0-12.0	41	20	21	41			2.617				0.40	0.76					С
7	12.0-14.0				45							0.20	0.29					
8	14.0-16.0				34							0.15	0.76					
9	16.0-18.0				35	90	121					0.15	0.57	UU	6	0.35	Α	
10	18.0-20.0				50							0.20	0.33					
11	23.0-25.0	43	21	22								0.25						
12	28.0-30.0				74	56	98					0.25		UU	10	0.33	Α	
13	33.0-35.0											0.15						
14	38.0-40.0				31					92		0.10						
No.											T./DE	05.54		OTUE	D TEST I	VDEO		<u> </u>

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pHR = Resistivity CI = Chlorides



SUMMARY OF TEST RESULTS - BORING B-07

(TE-0138, Task 1)

LELAP Lab ID #10001

Terrebonne Parish, Louisiana

Project No. 04.55174066

PLATE B-1g

					lde	entificati	on Tests				Field She Strength Es	ear timate	Miniature Vane Tests	C	Compressi	on Tests		
Sample No.	Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1	0.0-2.0				12					59			0.58					
2	2.0-4.0	23	21	2	27								0.44					
4	6.0-6.0				31					29								
5	8.0-10.0	56	19	37	45							0.25	0.58					
6	10.0-12.0				38	86	118					0.20	0.33	UU	3	0.37	Α	
7	12.0-14.0				38							0.50	0.55					
8	14.0-16.0	43	20	23	35			2.599				0.35	0.31					С
9	16.0-18.0				38							0.40	0.18					
10	18.0-20.0				43	80	115					0.25	0.41	UU	7	0.35	Α	
11	23.0-25.0	80	26	54								0.30						
12	28.0-30.0				73	60	103					0.50		UU	10	0.38	В	
13	33.0-35.0											0.20						
14	38.0-40.0	23	21	2								0.20						
							חר אר דו	-0-			T) (D)	0	ILLIDE	OTUE	D TECT T	7/050		

-fugro

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane

C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pH

R = Resistivity CI = Chlorides



SUMMARY OF TEST RESULTS - BORING B-08

(TE-0138, Task 1)

LELAP Lab ID #10001

Project No. Terrebonne Parish, Louisiana PLATE B-1h 04.55174066

					lde	entificati	on Tests				Field Sho Strength Es	ear timate	Miniature Vane Tests	C	Compressi	on Tests		
Sample No.	Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1	0.0-2.0	82	24	58	44							0.08	0.18					
2	2.0-4.0				20													
3	4.0-5.5				14					33								
5	8.0-9.5	47	22	25														
6	10.0-12.0	46	21	25	31							0.15	0.24					С
7	12.0-14.0				39	88	122					0.15	0.43	UU	5	0.48	Α	
8	14.0-16.0				49							0.30	0.72					
9	16.0-18.0	62	24	38	53							0.20	0.75					
10	18.0-20.0				48	75	112					0.15	0.58	UU	7	0.47	Α	
11	23.0-25.0				60	65	104					0.20		UU	9	0.31	Α	
12	28.0-30.0											0.20						
13	33.0-35.0				35	91	123					0.15		UU	12	0.44	Α	
14	38.0-40.0											0.20						
		1	!		1	T) 4			!		T. (2)			0.71.15				L

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pH

R = Resistivity CI = Chlorides



SUMMARY OF TEST RESULTS - BORING B-09

(TE-0138, Task 1)

LELAP Lab ID #10001

Project No. Terrebonne Parish, Louisiana PLATE B-1i 04.55174066

					lde	entificati	on Tests				Field Sho Strength Es	ear timate	Miniature Vane Tests	(Compressi	on Tests		
Sample No.	Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)		Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1	0.0-2.0				31								0.07					
2	2.0-4.0				28					50								
3	4.0-5.5																	
4	6.0-7.5	25	24	1														
5	8.0-9.0				61													
	9.0-10.0											0.10	0.34					
6	10.0-12.0	81	27	54	111							0.18	0.49					
7	12.0-14.0				30							0.35						
8	14.0-16.0				113							0.60	0.32					
No	tos:		1		<u> </u>		DE OE TI	L	1	<u> </u>	TVDE			OTUE	 :D TEST 1	VDES		

-fugeo

NP = Non-Plastic Material

TYPE OF TEST

Bayou De Cade Marsh Creation and Ridge Restoration

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pH

R = Resistivity CI = Chlorides



SUMMARY OF TEST RESULTS - BORING B-10

(TE-0138, Task 1)

LELAP Lab ID #10001

Project No. Terrebonne Parish, Louisiana PLATE B-1j 04.55174066

					lde	entificati	on Tests				Field Sho Strength Es	ear timate	Miniature Vane Tests	C	Compressi	on Tests		
Sample No.	Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1	0.0-2.0				86							0.20	0.07					
2	2.0-4.0				26					83		0.20	0.08					
3	4.0-6.0	84	25	59	85							0.20	0.11					
4	6.0-8.0				64							0.30	0.14					
5	8.0-10.0				74							0.40	0.19					
6	10.0-12.0				63							0.40	0.18					
7	12.0-14.0	56	20	36	62							0.35	0.27					
8	14.0-16.0				61							0.30	0.34					
No.	itos:	.1	1	-			DE OE TI	-ст	I.		TVDE			OTUE	D TEST T	VDEC		

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pH

R = Resistivity CI = Chlorides



Bayou De Cade Marsh Creation and Ridge Restoration

SUMMARY OF TEST RESULTS - BORING B-11

(TE-0138, Task 1)

Terrebonne Parish, Louisiana

Project No.

PLATE B-1k 04.55174066

LELAP Lab ID #10001

					lde	entificati	on Tests				Field Sho Strength Es	ear timate	Miniature Vane Tests	C	Compressi	on Tests		
Sample No.	Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1	0.0-2.0				82							0.20	0.14					
2	2.0-4.0	61	23	38	35							0.30	0.10					
3	4.0-6.0				32							0.25	0.18					
4	6.0-7.5				30					35								
5	8.0-9.0																	
	9.0-10.0				28													
6	10.0-11.5				32					53								
7	12.0-13.5																	
8	14.0-16.0				386				24.28			0.30	0.61					
N1.			•	•	•		חב אב דו			•	T) (D)	. OF EA		07115	D TECT T	7.050		

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pH

R = Resistivity CI = Chlorides



Bayou De Cade Marsh Creation and Ridge Restoration

SUMMARY OF TEST RESULTS - BORING B-12

LELAP Lab ID #10001

(TE-0138, Task 1)

Project No. Terrebonne Parish, Louisiana PLATE B-11 04.55174066

					lde	entificati	on Tests				Field Sho Strength Es	ear timate	Miniature Vane Tests	C	Compressi	on Tests		
Sample No.	Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1	0.0-2.0				25					84			1.43					
2	2.0-3.5																	
3	4.0-5.5																	
4	6.0-8.0				28					52		0.25	0.23					
5	8.0-9.0																	
	9.0-10.0				40							0.50	0.33					
6	10.0-12.0	123	38	85	82							0.20	0.41					
7	12.0-14.0				162							0.20	0.38					
8	14.0-16.0				206				42.98			0.25	0.59					
	.4		1	L	-				ļ									

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pH

R = Resistivity CI = Chlorides



SUMMARY OF TEST RESULTS - BORING B-13

(TE-0138, Task 1)

LELAP Lab ID #10001

Terrebonne Parish, Louisiana

Project No. 04.55174066

PLATE B-1m

Sample No.	Depth (ft)	Identification Tests									Field Shear Strength Estimate		Miniature Vane Tests	Compression Tests				
		Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1	0.0-2.0				48							0.15	0.16					
2	2.0-4.0	79	26	53	86							0.05	0.09					
3	4.0-6.0				53					99		0.05	0.07					
5	8.0-10.0				93							0.20	0.05					
6	10.0-12.0				144							0.30	0.02					
7	12.0-14.0	165	47	118	185							0.30	0.14					
8	14.0-16.0				170							0.35	0.14					
																		-
	ites:		<u> </u>		<u> </u>		DE OE TI		1		T\/D=			OT: ::	D TEST T	VDEO		

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pH

R = Resistivity CI = Chlorides



Bayou De Cade Marsh Creation and Ridge Restoration

SUMMARY OF TEST RESULTS - BORING B-14

(TE-0138, Task 1)

Project No.

PLATE B-1n

LELAP Lab ID #10001

Terrebonne Parish, Louisiana

04.55174066

					lde	entificati	on Tests				Field Sho Strength Es	ear timate	Miniature Vane Tests	C	Compressi	on Tests		
Sample No.	Depth (ft)	Liquid Limit (%)	Plastic Limit (%)	Plasticity Index (PI)	Moisture Content (%)	Dry Unit Weight (pcf)	Total Unit Weight (pcf)	Specific Gravity	Organic Content (%)	Passing No. 200 Sieve (%)	Penetrometer (ksf)	Torvane (ksf)	Shear Strength (ksf)	Type Test	Confining Pressure (psi)	Shear Strength (ksf)	Type of Failure	Other Tests
1	0.0-2.0				71							0.30	0.11					
2	2.0-4.0				40					93			0.17					
4	4.0-6.0	87	26	61														
4	6.0-8.0				103							0.40	0.21					
5	8.0-10.0				36					79		0.40	0.29					
6	10.0-12.0				102							0.40	0.14					
7	12.0-14.0	87	28	59	71							0.45	0.18					
9	16.0-18.0				64							0.30	0.19					
	400.	1			-			-0-	1		T. (2)			0.71.15				<u> </u>

Notes:

NP = Non-Plastic Material

TYPE OF TEST

U - Unconfined Compression
UU - Unconsolidated - Undrained Triaxial

CU - Consolidated - Undrained Triaxial

TYPE OF FAILURE

A - Bulge

B - Single Shear Plane C - Multiple Shear Plane D - Vertical Fracture

OTHER TEST TYPES

C = Consolidation SO = Sulfates

pH = pH

R = Resistivity CI = Chlorides



Bayou De Cade Marsh Creation and Ridge Restoration

SUMMARY OF TEST RESULTS - BORING B-15


(TE-0138, Task 1)

LELAP Lab ID #10001

Terrebonne Parish, Louisiana

Project No. 04.55174066

PLATE B-10



Remarks: All tests were performed in general accordance with ASTM Standards D4318, D421, D2217, and D1140. Fines column represent % passing No. 200 sieve.



ATTERBERG LIMITS CHART

Bayou De Cade Marsh Creation and Ridge
Restoration


ATTERBERG LIMITS' RESULTS

(TE-0138, Task 1)

Terrebonne Parish, Louisiana

Project No. 04.55174066

PLATE B-2a



ASTM Standards D4318, D421, D2217, and D1140. Fines column represent % passing No. 200 sieve.



ATTERBERG LIMITS CHART

Bayou De Cade Marsh Creation and Ridge Restoration


ATTERBERG LIMITS' RESULTS

(TE-0138, Task 1)

Terrebonne Parish, Louisiana

Project No. 04.55174066

PLATE B-2b



ASTM Standards D4318, D421, D2217, and D1140. Fines column represent % passing No. 200 sieve.



ATTERBERG LIMITS CHART

Bayou De Cade	Marsh	Creation	and Ridge
Restoration			


ATTERBERG LIMITS' RESULTS

(TE-0138, Task 1)

Terrebonne Parish, Louisiana

Project No. 04.55174066

PLATE B-2c



Remarks: All tests were performed in general accordance with ASTM Standards D4318, D421, D2217, and D1140. Fines column represent % passing No. 200 sieve.



ATTERBERG LIMITS CHART

Bayou De Cade Marsh Creation and Ridge Restoration


ATTERBERG LIMITS' RESULTS


(TE-0138, Task 1)


Terrebonne Parish, Louisiana


Project No. 04.55174066


PLATE B-2d

























1				
F	Ridge Rest	Cade Marsh oration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
[Source of Sample: B-01		Depth: 18-20 ft.	Visual Classification:
[Sample Number: 10			FAT CLAY (CH), gray, with silty sand pockets
L	Project No.: 04.55174066	Tes	t Date.: 4/17/201	Organic Content (%) ASTM D2974: N/A
ı	Sample No.	1 ●	2 ■ 3 ▲	
INITIAL	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assumed	43.9 78.7 100.0 1.14 2.84 5.77 d) 2.70 1.0		Remarks: Visual classification in general accordance with ASTM Standard D2487.
	Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) The proof of t	5.00 516 258 14.8 1236 720		
	Failure Type:	Bulging	Failure Sketch	




PLATE B-4a



Project Name: Bayou De Ridge Res Terrebonn	Cade Marsh toration e Parish, Lo		Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-01		Depth: 33-35 ft.	Visual Classification:
Sample Number: 13			FAT CLAY (CH), gray, with sand lenses and pockets
Project No.: 04.55174066	Tes	st Date.: 4/20/2018	Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2 ■ 3 ▲	
Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	41.2 80.4 100.0 1.10 2.83 5.57		Remarks: Visual classification in general accordance with ASTM Standard D2487.
Strain Rate (%/min.) Cell Pressure (psi)	1.0 9.00		
Deviator Stress (psf)	574		
Shear Strength (psf) Failure Strain (%)	287 14.3		
O ₁ Failure (psf): O ₃ Failure (psf):	1870 1296		
Failure Type:	Bulging	Failure Sketch	




PLATE B-4b



1					
	Ridge Rest	Cade Marsh oration e Parish, Lou		and	Type of Test: Unconsolidated Undrained ASTM D 2850
[Source of Sample: B-01		Depth: 3	8-40 ft.	Visual Classification:
	Sample Number: 14				FAT CLAY (CH), gray, with sand lenses and pockets
Ц	Project No.: 04.55174066	Tes	t Date.: 4	/20/2018	Organic Content (%) ASTM D2974: N/A
ı	Sample No.	1 ●	2 ■	3 ▲	
	Water Content (%)	58.9			Remarks:
ı	Dry Density (pcf)	68.9			Visual classification in general accordance with ASTM Standard D2487.
با	Saturation (%)	100.0			
NITIA	Void Ratio	1.45			
Z	Diameter (inches)	1.41			
ı	Height (inches)	2.96			
ı	% Passing #200 Sieve				
	Specific Gravity (assume	d) 2.70			
ı	Strain Rate (%/min.)	1.0			
ı	Cell Pressure (psi)	11.00			
ı	Deviator Stress (psf)	898			
ı	Shear Strength (psf)	449			
	Failure Strain (%)	4.2	1		
1	ປ ₁ Failure (psf):	2482			
	ິງ Failure (psf):	1584			
	Failure Type:	Bulging	Failure S	ketch	




PLATE B-4c



L				
	Ridge Rest	Cade Marsh oration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
-	Source of Sample: B-01		Depth: 53-55 ft.	Visual Classification:
-	Sample Number: 17			FAT CLAY (CH), gray
П	Project No.: 04.55174066	Tes	t Date.: 4/20/2018	Organic Content (%) ASTM D2974: N/A
	Sample No.	1 ●	2 ■ 3 ▲	
	Water Content (%)	67.3		Remarks:
ı	Dry Density (pcf)	59.5		Visual classification in general accordance with ASTM Standard D2487.
_	Saturation (%)	99.2		
NITA	Void Ratio	1.83		
Z	Diameter (inches)	2.84		
ı	Height (inches)	5.58		
ı	% Passing #200 Sieve			
L	Specific Gravity (assume	d) 2.70		
ı	Strain Rate (%/min.)	1.0		
ı	Cell Pressure (psi)	15.00		
ı	Deviator Stress (psf)	890	\lambda \ \ \ \ \	
ı	Shear Strength (psf)	445		
Failure Strain (%)		8.3		
o ₁ Failure (psf):		3050		
	σ ₃ Failure (psf):	2160		
	Failure Type:	Multi Shear	Failure Sketch	




PLATE B-4d



Ridge Resi	Cade Marsh toration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-02		Depth: 18-20 ft.	Visual Classification:
Sample Number: 10			FAT CLAY (CH), gray, with a 2-inch sand layer
Project No.: 04.55174066	Tes	t Date.: 4/20/2018	Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2 ■ 3 ▲	
Water Content (%)	67.0		Remarks:
Dry Density (pcf)	59.1		Visual classification in general accordance with ASTM Standard D2487.
Saturation (%)	97.8		Ţ
Void Ratio Diameter (inches)	1.85		
☑ Diameter (inches)	2.85		
Height (inches)	5.58		
% Passing #200 Sieve			
Specific Gravity (assume	d) 2.70		
Strain Rate (%/min.)	1.0		
Cell Pressure (psi)	5.00		
Deviator Stress (psf)	636	λ ,\	
Shear Strength (psf)	318		
Failure Strain (%)	8.0		
O ₁ Failure (psf):	1356		
O ₃ Failure (psf):	720		
Failure Type:	Multi Shear	Failure Sketch	




PLATE B-4e



Failure Type:

TRIAXIAL SHEAR TEST

			,
	ridge Rest	Cade Marsh Creation and toration e Parish, Louisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
	Source of Sample: B-02	Depth: 28-30 ft.	Visual Classification:
L	Sample Number: 12		LEAN CLAY (CL), gray, with peat layers
L	Project No.: 04.55174066	Test Date.: 4/25/2018	Organic Content (%) ASTM D2974: N/A
	Sample No.	1 ● 2 ■ 3 ▲	
INITIA	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	29.3 74.9 63.3 1.25 2.84 5.55	Remarks: Visual classification in general accordance with ASTM Standard D2487.
	Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) O 1 Failure (psf): O 3 Failure (psf):	1.0 8.00 400 200 13.5 1552 1152	




PLATE B-4f



1				
	ridge Rest	Cade Marsh oration e Parish, Lo	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
	Source of Sample: B-02		Depth: 48-50 ft.	Visual Classification:
	Sample Number: 16			FAT CLAY (CH), gray, with silty sand layers
	Project No.: 04.55174066	Tes	st Date.: 4/25/2018	Organic Content (%) ASTM D2974: N/A
Г	Sample No.	1 ●	2 ■ 3 ▲	
IAITINI	Height (inches) % Passing #200 Sieve Specific Gravity (assume			Remarks: Visual classification in general accordance with ASTM Standard D2487.
	Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) O 1 Failure (psf): O 3 Failure (psf):	1.0 13.00 800 400 13.5 2672 1872		
ı	Failure Type:	Bulging	Failure Sketch	




PLATE B-4g



Ridge Res	Cade Marsh toration e Parish, Lo	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-03		Depth: 12-14 ft.	Visual Classification:
Sample Number: 7			LEAN CLAY (CL), gray
Project No.: 04.55174066	Tes	st Date.: 4/27/2018	Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2 ■ 3 ▲	
Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	39.4 86.1 100.0 0.96 2.83 5.40		Remarks: Visual classification in general accordance with ASTM Standard D2487.
Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) O 1 Failure (psf): O 3 Failure (psf):	1.0 5.00 688 344 14.5 1408 720		
Failure Type:	Bulging	Failure Sketch	




PLATE B-4h



Ridge Rest	Cade Marsh toration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-03		Depth: 16-18 ft.	Visual Classification:
Sample Number: 9			LEAN CLAY (CL), gray, with organic traces
Project No.: 04.55174066	Tes	t Date.: 4/27/2018	Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2 ■ 3 ▲	
Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume Strain Rate (%/min.) Cell Pressure (psi)	80.7 54.3 100.0 2.11 2.82 5.61 d) 2.70 1.0 6.00		Remarks: Visual classification in general accordance with ASTM Standard D2487.
Deviator Stress (psf) Shear Strength (psf) Failure Strain (%)	772 386 5.5		
O ₁ Failure (psf): O ₃ Failure (psf):	1636 864		
Failure Type:	Multi Shear	Failure Sketch	




PLATE B-4i



Ridge Rest	Cade Marsh toration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-03		Depth: 24.2-25 ft.	Visual Classification:
Sample Number:			FAT CLAY (CH), gray, with silt pockets and organics
Project No.: 04.55174066	Tes	t Date.: 4/27/2018	Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2 ■ 3 ▲	
Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	68.7 58.3 98.0 1.89 2.82 5.58		Remarks: Visual classification in general accordance with ASTM Standard D2487.
Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) O 1 Failure (psf): O 3 Failure (psf):	1.0 9.00 596 298 14.4 1892 1296		
Failure Type:	Bulging	Failure Sketch	




PLATE B-4j



	Ridge Rest	Cade Marsh oration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850	
	Source of Sample: B-03		Depth: 38-40 ft.	Visual Classification:	
	Sample Number: 14			FAT CLAY (CH), gray, with sand layers	
	Project No.: 04.55174066	Tes	t Date.: 4/27/2018	Organic Content (%) ASTM D2974: N/A	
	Sample No.	1 ●	2 ■ 3 ▲		
INITIAI	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assumed	52.8 70.6 100.0 1.39 2.80 5.59		Remarks: Visual classification in general accordance with ASTM Standard D2487.	
	Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) O 1 Failure (psf): O 3 Failure (psf):	1.0 14.00 931 465 15.0 2947 2016			
	Failure Type:	Bulging	Failure Sketch		




PLATE B-4k



L					
	Project Name: Bayou De Cade Marsh Creation and Ridge Restoration Terrebonne Parish, Louisiana				Type of Test: Unconsolidated Undrained ASTM D 2850
-	Source of Sample: B-03		Depth: 48-50	Oft.	Visual Classification:
	Sample Number: 16				FAT CLAY (CH), gray, with organic traces
П	Project No.: 04.55174066	Tes	t Date.: 5/3/2	2018	Organic Content (%) ASTM D2974: N/A
	Sample No.	1 ●	2 ■ 3	A	
INITIAL	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	59.7 68.9 100.0 1.45 1.46 2.83			Remarks: Visual classification in general accordance with ASTM Standard D2487.
•	Strain Rate (%/min.)	1.0			
	Cell Pressure (psi)	17.00			
ı	Deviator Stress (psf)	1142			
ı	Shear Strength (psf)	571			
	Failure Strain (%)	12.5			
	O ₁ Failure (psf):	3590			
	O ₃ Failure (psf):	2448			
	Failure Type:	45° Shear	Failure Sketch	1	




PLATE B-41



	Ridae Rest	Cade Marsh oration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
	Source of Sample: B-03		Depth: 58-60 ft.	Visual Classification:
	Sample Number: 18			FAT CLAY (CH), gray
	Project No.: 04.55174066	Tes	t Date.: 5/3/2018	Organic Content (%) ASTM D2974: N/A
	Sample No.	1 ●	2 ■ 3 ▲	
IAITINI	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assumed	69.7 59.1 100.0 1.85 2.83 5.65		Remarks: Visual classification in general accordance with ASTM Standard D2487.
r	Strain Rate (%/min.)	1.0		
ı	Cell Pressure (psi)	21.00		
ı	Deviator Stress (psf)	1176		
ı	Shear Strength (psf)	588		
ı	Failure Strain (%)	1.9		
	5 1 Failure (psf): 4200			
	O ₃ Failure (psf):	3024		
1	Failure Type:	45° Shear	Failure Sketch	




PLATE B-4m



Project Name: Bayou De Cade Marsh Creation and Ridge Restoration Terrebonne Parish, Louisiana				Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-04		Depth: 6	5-8 ft.	Visual Classification:
Sample Number: 4				FAT CLAY (CH), brown and gray, with silt pockets and layers
Project No.: 04.55174066	Tes	st Date.: 5	5/3/2018	Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2	3 ▲	
Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	40.8 84.8 100.0 0.99 2.79 5.63			Remarks: Visual classification in general accordance with ASTM Standard D2487.
Strain Rate (%/min.)	1.0			
Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) O 1 Failure (psf): O 3 Failure (psf):	3.00 750 375 14.9 1182 432			
Failure Type:	Bulging	Failure S	ketch	




PLATE B-4n



1				
	ridge Rest	Cade Marsh oration e Parish, Lo	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
	Source of Sample: B-04		Depth: 12-14 ft.	Visual Classification:
	Sample Number: 7			FAT CLAY (CH), gray
	Project No.: 04.55174066	Tes	st Date.: 5/4/2018	Organic Content (%) ASTM D2974: N/A
Г	Sample No.	1 ●	2 ■ 3 ▲	
•	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assumed) Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf)	33.0 87.2 95.6 0.93 2.87 5.16 d) 2.70 1.0 5.00 490 245		Remarks: Visual classification in general accordance with ASTM Standard D2487.
•	Failure Strain (%) O 1 Failure (psf):	15.0 1210	\/	
	O ₃ Failure (psf):	720		
ı	Failure Type:	Bulging	Failure Sketch	




PLATE B-40



	Project Name: Bayou De 0 Ridge Rest Terrebonne	Cade Marsh oration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
-	Source of Sample: B-04		Depth: 23-25 ft.	Visual Classification:
,	Sample Number: 11			FAT CLAY (CH), gray
	Project No.: 04.55174066	Tes	t Date.: 5/4/2018	Organic Content (%) ASTM D2974: N/A
ı	Sample No.	1 ●	2 ■ 3 ▲	
NITIAL	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume			Remarks: Visual classification in general accordance with ASTM Standard D2487.
	Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) Congress Failure (psf):	1.0 9.00 444 222 15.0 1740 1296		
	Failure Type:	Bulging	Failure Sketch	




PLATE B-4p



Ridge Resi	Cade Marsh toration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-04		Depth: 33-35 ft.	Visual Classification:
Sample Number: 13			LEAN CLAY (CL), gray, with silt and sand pockets
Project No.: 04.55174066	Tes	t Date.: 5/7/2018	Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2 ■ 3 ▲	
Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	45.2 79.0 100.0 1.13 2.79 5.52		Remarks: Visual classification in general accordance with ASTM Standard D2487.
Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) O 1 Failure (psf): O 3 Failure (psf):	1.0 12.00 687 344 15.0 2415 1728		
Failure Type:	Multi Shear	Failure Sketch	




PLATE B-4q



Ridge Rest	Cade Marsh coration e Parish, Lo	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-05		Depth: 2-4 ft.	Visual Classification:
Sample Number: 2			FAT CLAY (CH), gray, with organics
Project No.: 04.55174066	Tes	st Date.: 4/24/2018	Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2 ■ 3 ▲	
Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	51.8 71.2 100.0 1.37 2.81 5.60		Remarks: Visual classification in general accordance with ASTM Standard D2487.
Strain Rate (%/min.) Cell Pressure (psi)	1.0		
Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) O 1 Failure (psf):	770 385 14.6 1202		
O ₃ Failure (psf): Failure Type:	432 Bulging	Failure Sketch	




PLATE B-4r



1						
	ridge Rest	Cade Marsh oration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850		
[Source of Sample: B-05		Depth: 8-10 ft.	Visual Classification:		
[Sample Number: 5			LEAN CLAY (CL), gray		
	Project No.: 04.55174066	Tes	t Date.: 4/24/2018	Organic Content (%) ASTM D2974: N/A		
	Sample No.	1 ●	2 ■ 3 ▲			
INITIAL	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assumed	33.3 87.5 97.1 0.93 2.81 5.58		Remarks: Visual classification in general accordance with ASTM Standard D2487.		
	Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) To 1 Failure (psf): To 3 Failure (psf):	1.0 3.00 1394 697 15.0 1826 432				
L	Failure Type:	Bulging	Failure Sketch			




PLATE B-4s



Pr	Ridge Rest	Cade Marsh oration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
Sc	ource of Sample: B-05		Depth: 14-16 ft.	Visual Classification:
Sa	ample Number: 8			LEAN CLAY (CL), gray, with silt pockets
Pr	oject No.: 04.55174066	Tes	t Date.: 4/24/2018	Organic Content (%) ASTM D2974: N/A
	Sample No.	1 ●	2 ■ 3 ▲	
INITIAL	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	52.2 72.0 100.0 1.34 2.83 5.57		Remarks: Visual classification in general accordance with ASTM Standard D2487.
St C	train Rate (%/min.) ell Pressure (psi) eviator Stress (psf)	1.0 5.00 698		
Fa	Shear Strength (psf) ailure Strain (%)	349 14.1 1418		
σ	1 Failure (psf): 3 Failure (psf): ailure Type:	720 Bulging	Failure Sketch	




PLATE B-4t



Ridge Res	Cade Marsh toration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-05		Depth: 23-25 ft.	Visual Classification:
Sample Number: 11			LEAN CLAY (CL), gray, with wood and silt pockets
Project No.: 04.55174066	Tes	t Date.: 4/25/2018	Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2 ■ 3 ▲	
Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	33.4 88.6 100.0 0.90 2.83 5.53		Remarks: Visual classification in general accordance with ASTM Standard D2487.
Strain Rate (%/min.)	1.0		1
Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf)	7.00 1666 833		
Failure Strain (%) O 1 Failure (psf):	15.0 2674		
O ₃ Failure (psf):	1008		
Failure Type:	Bulging	Failure Sketch	




PLATE B-4u



Project Name: Bayou De Cade Marsh Creation and Ridge Restoration Terrebonne Parish, Louisiana			Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-06 Depth: 4-6 ft.		Depth: 4-6 ft.	Visual Classification:
Sample Number: 3			LEAN CLAY (CL), gray, with silt pockets and roots
Project No.: 04.55174066	Tes	t Date.: 4/25/2018	Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2 ■ 3 ▲	
Height (inches) % Passing #200 Sieve	35.4 87.5 100.0 0.92 2.84 5.56		Remarks: Visual classification in general accordance with ASTM Standard D2487.
O ₃ Failure (psf):	1.0 3.00 656 328 14.6 1088 432		
	Ridge Rest Terrebonne Source of Sample: B-06 Sample Number: 3 Project No.: 04.55174066 Sample No. Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) We Passing #200 Sieve Specific Gravity (assumed Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) Tailure (psf):	Ridge Restoration Terrebonne Parish, Lou Source of Sample: B-06 Sample Number: 3 Project No.: 04.55174066 Tes Sample No. 1 ● Water Content (%) 35.4 Dry Density (pcf) 87.5 Saturation (%) 100.0 Void Ratio 0.92 Diameter (inches) 2.84 Height (inches) 5.56 % Passing #200 Sieve Specific Gravity (assumed) 2.70 Strain Rate (%/min.) 1.0 Cell Pressure (psi) 3.00 Deviator Stress (psf) 656 Shear Strength (psf) 328 Failure Strain (%) 14.6 □ 1 Failure (psf): 1088 □ 3 Failure (psf): 432	Ridge Restoration Terrebonne Parish, Louisiana Source of Sample: B-06 Sample Number: 3 Project No.: 04.55174066 Sample No. Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) Passing #200 Sieve Specific Gravity (assumed) Deviator Stress (psf) Shear Strength (psf) Failure (psf): ¬ Failure (psf): Source of Sample: B-06 Depth: 4-6 ft. Depth: 4-6 ft. Depth: 4-6 ft. Depth: 4-6 ft. Past Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018 Test Date: 4/25/2018




PLATE B-4v



TRIAXIAL SHEAR TEST

L				
Ī	Project Name: Bayou De 0 Ridge Rest Terrebonne	Cade Marsh Cr oration Parish, Louis	reation and iana	Type of Test: Unconsolidated Undrained ASTM D 2850
,	Source of Sample: B-06	De	epth: 8-10 ft.	Visual Classification:
	Sample Number: 5			LEAN CLAY (CL), gray, with silt pockets
	Project No.: 04.55174066	Test D	ate.: 4/26/2018	Organic Content (%) ASTM D2974: N/A
	Sample No.	1 •	2 ■ 3 ▲	
INITIAL	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assumed	42.7 80.7 100.0 1.09 2.81 5.56		Remarks: Visual classification in general accordance with ASTM Standard D2487.
ı	Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf)	1.0 3.00 1196		
	Shear Strength (psf) Failure Strain (%)	598 8.0		
	の ₁ Failure (psf): の ₃ Failure (psf):	1628 432		




PLATE B-4w



TRIAXIAL SHEAR TEST

1					
	Project Name: Bayou De Cade Marsh Creation and Ridge Restoration Terrebonne Parish, Louisiana				Type of Test: Unconsolidated Undrained ASTM D 2850
	Source of Sample: B-06		Depth:	14-16 ft.	Visual Classification:
	Sample Number: 8				LEAN CLAY (CL), gray, with silt pockets
	Project No.: 04.55174066	Tes	t Date.:	4/26/2018	Organic Content (%) ASTM D2974: N/A
	Sample No.	1 ●	2	3 ▲	
IAITINI	Height (inches) % Passing #200 Sieve	65.6 63.0 100.0 1.67 2.83 5.58			Remarks: Visual classification in general accordance with ASTM Standard D2487.
	Specific Gravity (assumed Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) O 1 Failure (psf): O 3 Failure (psf):	2.70 1.0 5.00 594 297 12.3 1314 720			




PLATE B-4x



TRIAXIAL SHEAR TEST

l r	you De Cade Mars Ige Restoration rrebonne Parish, L		Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample:	B-06	Depth: 38-40 f	Visual Classification:
Sample Number:	14		FAT CLAY (CH), gray, with silt pockets
Project No.: 04.55	174066 T	est Date.: 4/26/20	18 Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2 ■ 3 ▲	
Water Content (% Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches Height (inches) % Passing #200 Specific Gravity (72.5 100.0 1.32) 2.81 5.62 Sieve assumed) 2.70		Remarks: Visual classification in general accordance with ASTM Standard D2487.
Strain Rate (%/mir Cell Pressure (psi) Deviator Stress (psi Shear Strength Failure Strain (%) O 1 Failure (psf): O 3 Failure (psf):	11.00 sf) 1072		




PLATE B-4y



TRIAXIAL SHEAR TEST

Project Name: Bayou De C Ridge Rest Terrebonne	Cade Marsh Creoration Parish, Louisia	eation and ana	Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-06	De	pth: 48-50 ft.	Visual Classification: FAT CLAY (CH), gray, with silt pockets
Sample Number: 17			FAT CLAT (CH), gray, with sin pockets
Project No.: 04.55174066	Test D	ate.: 4/26/2018	Organic Content (%) ASTM D2974: N/A
Sample No.	1 ● 2	2 ■ 3 ▲	
Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	66.7 60.8 100.0 1.77 2.83 5.62		Remarks: Visual classification in general accordance with ASTM Standard D2487.
Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) The properties of	1.0 14.00 940 470 6.4 2956 2016		
	Ridge Rest Terrebonne Fource of Sample: B-06 Fample Number: 17 Froject No.: 04.55174066 Sample No. Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assumed Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%)	Ridge Restoration Terrebonne Parish, Louisia Fource of Sample: B-06 Fample Number: 17 Froject No.: 04.55174066 Sample No. Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Void Ratio 1.77 Diameter (inches) Height (inches) Passing #200 Sieve Specific Gravity (assumed) Strain Rate (%/min.) Dell Pressure (psi) Shear Strength (psf) Failure Strain (%) Tambot Content (%) Ridge Restoration Del Content (Parish, Louisia Test D 66.7 Test D 66.7 60.8 100.0 22 23 44.00 24 470 470 470 470 470 470 47	Ridge Restoration Terrebonne Parish, Louisiana Source of Sample: B-06 Cample Number: 17 Project No.: 04.55174066 Sample No. Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Void Ratio 1.77 Diameter (inches) Height (inches) Specific Gravity (assumed) Specific Gravity (assumed) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) Failure (psf): Depth: 48-50 ft. Depth: 48-50 ft. Depth: 48-50 ft. Depth: 48-50 ft. Beth: 4/26/2018 Test Date.: 4/26




PLATE B-4z



Project Name: Bayou De (Cade Marsh	Constitute and	T (T)
Terrebonne	oration e Parish, Lou	uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-07		Depth: 0-2 ft.	Visual Classification:
Sample Number: 1			FAT CLAY (CH), gray, with silt pockets
Project No.: 04.55174066	Tes	t Date.: 5/7/20	8 Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2■ 3	
Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	59.1 65.9 100.0 1.56 2.82 5.57		Remarks: Visual classification in general accordance with ASTM Standard D248
Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) The properties of	1.0 3.00 446 223 14.8 878 432		
	cample Number: 1 Project No.: 04.55174066 Sample No. Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assumer Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%)	Eample Number: 1 Project No.: 04.55174066 Sample No. Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) Specific Gravity (assumed) Strain Rate (%/min.) Cell Pressure (psi) Shear Strength (psf) Saturation (%) Shear Strain (%) Saturation (%) Shear Strain (%) Saturation (%) Shear Strain (%) Saturation (%	Sample Number: 1 Project No.: 04.55174066 Test Date.: 5/7/2018 Sample No. 1 ● 2 ■ 3 ▲ Water Content (%) 59.1 Dry Density (pcf) 65.9 Saturation (%) 100.0 Void Ratio 1.56 Diameter (inches) 2.82 Height (inches) 5.57 % Passing #200 Sieve 5.57 Specific Gravity (assumed) 2.70 Strain Rate (%/min.) 1.0 Deviator Stress (psf) 3.00 Deviator Stress (psf) 446 Shear Strength (psf) 223 Failure Strain (%) 14.8 Tailure (psf): 878 Tailure (psf): 432




PLATE B-4aa



Project Name: Bayou De Cade Marsh Creation and Ridge Restoration Terrebonne Parish, Louisiana					Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sampl	e: B-07		Depth: 8	3-10 ft.	Visual Classification:
Sample Number:	5				FAT CLAY (CH), gray, with silt pockets
Project No.: 04.5	5174066	Tes	t Date.: 5	5/7/2018	Organic Content (%) ASTM D2974: N/A
Sample No.		1 ●	2	3 ▲	
Water Content Dry Density (po Saturation (%) Void Ratio Diameter (inch Height (inches) % Passing #20	es)	32.1 90.9 100.0 0.85 2.84 5.59			Remarks: Visual classification in general accordance with ASTM Standard D2487.
Specific Gravity		d) 2.70			
Strain Rate (%/m	nin.)	1.0			
Cell Pressure (pa	si)	3.00			
Deviator Stress (. ,	1381	1		
Shear Strengt		691		V	
Failure Strain (%		15.0			
σ ₁ Failure (psf		1813			
○ 3 Failure (psf):	432			
Failure Type:		Bulging	Failure S	sketch	




PLATE B-4ab



Ridge Res	Cade Marsh toration e Parish, Lo	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-07		Depth: 16-18 ft.	Visual Classification:
Sample Number: 9			FAT CLAY (CH), gray, with silt pockets
Project No.: 04.55174066	Tes	st Date.: 5/7/2018	Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2 ■ 3 ▲	
Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	35.1 89.7 100.0 0.88 2.79 5.53		Remarks: Visual classification in general accordance with ASTM Standard D2487.
Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf)	1.0 6.00 706		
Shear Strength (psf) Failure Strain (%)	353 14.3		
o 1 Failure (psf): o 3 Failure (psf):	1570 864		
Failure Type:	Bulging	Failure Sketch	




PLATE B-4ac



1					
	ridge Rest	Cade Marsh coration e Parish, Lo	Creation and uisiana	d	Type of Test: Unconsolidated Undrained ASTM D 2850
	Source of Sample: B-07		Depth: 28-3	30 ft.	Visual Classification:
	Sample Number: 12				FAT CLAY (CH), gray, with organics
	Project No.: 04.55174066	Tes	st Date.: 5/8/	2018	Organic Content (%) ASTM D2974: N/A
Г	Sample No.	1 ●	2	3 ▲	
IAITIN	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	73.6 56.3 99.5 2.00 2.82 5.56			Remarks: Visual classification in general accordance with ASTM Standard D2487.
	Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) O 1 Failure (psf): O 3 Failure (psf):	1.0 10.00 650 325 11.0 2090 1440			
	Failure Type:	Bulging	Failure Sketo	ch	




PLATE B-4ad



TRIAXIAL SHEAR TEST

1				
F	Project Name: Bayou De C Ridge Rest Terrebonne	Cade Marsh Creat toration e Parish, Louisiana	ion and	Type of Test: Unconsolidated Undrained ASTM D 2850
5	Source of Sample: B-08	Depth	n: 10-12 ft.	Visual Classification:
5	Sample Number: 6			FAT CLAY (CH), gray
F	Project No.: 04.55174066	Test Date	.: 5/8/2018	Organic Content (%) ASTM D2974: N/A
L	Sample No.	1 ● 2 ■	3 ▲	
INITIAL	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	37.6 85.9 100.0 0.96 2.80 5.59		Remarks: Visual classification in general accordance with ASTM Standard D2487.
(Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf) Shear Strength (psf) Failure Strain (%) The properties of	1.0 3.00 738 369 14.8 1170 432		




PLATE B-4ae



1				
	ridge Rest	Cade Marsh oration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
	Source of Sample: B-08		Depth: 18-20 ft.	Visual Classification:
	Sample Number: 10			FAT CLAY (CH), gray, with organics
	Project No.: 04.55174066	Tes	t Date.: 5/8/2018	Organic Content (%) ASTM D2974: N/A
	Sample No.	1 ●	2 ■ 3 ▲	
INITIAL	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	43.1 80.1 100.0 1.10 2.80 5.59		Remarks: Visual classification in general accordance with ASTM Standard D2487.
r	Strain Rate (%/min.)	1.0		-
ı	Cell Pressure (psi)	7.00		
ı	Deviator Stress (psf)	696		
ı	Shear Strength (psf)	348		
	Failure Strain (%)	11.8 1704		
	Tailure (psf):			
	Tailure (psf):	1008		
	Failure Type:	Bulging	Failure Sketch	




PLATE B-4af



	ridge Rest	Cade Marsh oration e Parish, Lou	Creation and iisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
-	Source of Sample: B-08		Depth: 28-30 ft.	Visual Classification:
	Sample Number: 12			FAT CLAY (CH), gray, with organics
П	Project No.: 04.55174066	Test	t Date.: 5/8/2018	Organic Content (%) ASTM D2974: N/A
	Sample No.	1 ●	2 ■ 3 ▲	
INITIAL	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	72.8 59.5 100.0 1.83 2.78 5.62		Remarks: Visual classification in general accordance with ASTM Standard D2487.
	Strain Rate (%/min.) Cell Pressure (psi)	1.0 10.00		
	Deviator Stress (psf)	758		
	Shear Strength (psf)	379		
•	Failure Strain (%)	5.0		
	o ₁ Failure (psf):	2198		
	O ₃ Failure (psf):	1440		
	Failure Type:	Shear Plane	Failure Sketch	




PLATE B-4ag



1				
	ridge Rest	Cade Marsh oration e Parish, Lo	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
Г	Source of Sample: B-09		Depth: 12-14 ft.	Visual Classification:
Г	Sample Number: 7			LEAN CLAY (CL), gray
	Project No.: 04.55174066	Tes	st Date.: 5/8/2018	Organic Content (%) ASTM D2974: N/A
Г	Sample No.	1 ●	2 ■ 3 ▲	
•	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assumed Strain Rate (%/min.) Cell Pressure (psi) Deviator Stress (psf)	39.4 87.6 100.0 0.92 2.82 5.39 d) 2.70 1.0 5.00 957		Remarks: Visual classification in general accordance with ASTM Standard D2487.
•	Shear Strength (psf) Failure Strain (%) O 1 Failure (psf):	478 15.0 1677		
	○ 3 Failure (psf):	720		
ı	Failure Type:	Bulging	Failure Sketch	




PLATE B-4ah



Ridae Res	Cade Marsh toration e Parish, Lo		and	Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-09		Depth: 18	3-20 ft.	Visual Classification:
Sample Number: 10				FAT CLAY (CH), gray
Project No.: 04.55174066 Test Date.: 5/8/2018			/8/2018	Organic Content (%) ASTM D2974: N/A
Sample No.	1 ●	2	3 ▲	
Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	48.5 75.2 100.0 1.24 2.81 5.61			Remarks: Visual classification in general accordance with ASTM Standard D2487.
Strain Rate (%/min.) Cell Pressure (psi)	1.0 7.00			
Deviator Stress (psf) Shear Strength (psf)	948 474			
Failure Strain (%) O 1 Failure (psf):	13.6 1956			
○ 3 Failure (psf):	1008			
Failure Type:	Bulging	Failure Sk	etch	




PLATE B-4ai



F	ridae Rest	Cade Marsh oration e Parish, Lou	Creation and uisiana	Type of Test: Unconsolidated Undrained ASTM D 2850
5	Source of Sample: B-09		Depth: 23-25 ft.	Visual Classification:
5	Sample Number:			FAT CLAY (CH), gray
F	Project No.: 04.55174066	Tes	t Date.: 5/8/2018	Organic Content (%) ASTM D2974: N/A
	Sample No.	1 ●	2 ■ 3 ▲	
INITIAL	Water Content (%) Dry Density (pcf) Saturation (%) Void Ratio Diameter (inches) Height (inches) % Passing #200 Sieve Specific Gravity (assume	59.9 65.3 100.0 1.58 2.84 5.59		Remarks: Visual classification in general accordance with ASTM Standard D2487.
K	Strain Rate (%/min.)	1.0		-
(Cell Pressure (psi)	9.00		
	Deviator Stress (psf)	617		
Ι.	Shear Strength (psf)	309		
•	Failure Strain (%)	15.0 1913		
	Failure (psf):			
	Failure (psf):	1296		
	Failure Type:	Bulging	Failure Sketch	




PLATE B-4aj



TRIAXIAL SHEAR TEST

Project Name: Bayou De Cade Marsh Creation and Ridge Restoration Terrebonne Parish, Louisiana					Type of Test: Unconsolidated Undrained ASTM D 2850
Source of Sample: B-09 Depth: 33-35 ft.				33-35 ft.	Visual Classification:
Sample Number	: 13				FAT CLAY (CH), gray
Project No.: 04.5	55174066	Tes	t Date.:	5/8/2018	Organic Content (%) ASTM D2974: N/A
Sample No.		1 ●	2	3 ▲	
Water Content Dry Density (po Saturation (%) Void Ratio Diameter (inch Height (inches) % Passing #20 Specific Gravity	es)) 0 Sieve y (assumed				Remarks: Visual classification in general accordance with ASTM Standard D2487.
Strain Rate (%/n Cell Pressure (p Deviator Stress (Shear Strengt Failure Strain (% O ₁ Failure (psf O ₃ Failure (psf	si) (psf) h (psf) b)	1.0 12.00 884 442 10.0 2612 1728			









PLATE B-4ak


























MATERIAL DESCRIPTION

FAT CLAY (CH)

TUGRO

Project No. 04.55174066 Client: CPRA


Project: Bayou De Cade Marsh Creation and Ridge Restoration

Source of Sample: Composite B-10 B-12 B-13 from mudline to depth of 10 ft

Remarks:

Test Date: 6/5/2018 Tested by: Jack Koban Reviewed by: Sam Bryant Specific Gravity test pending.

PLATE B-6a



MATERIAL DESCRIPTION

FAT CLAY (CH)

TUGRO (

Project No. 04.55174066 Client: CPRA

Project: Bayou De Cade Marsh Creation and Ridge Restoration

Source of Sample: Composite B-11 B-14 B-15 from mudline to depth of 10 ft

Remarks:

Test Date: 6/5/2018 Tested by: Jack Koban Reviewed by: Sam Bryant Specific Gravity test pending.

PLATE B-6b



APPENDIX B1 COLUMN SETTLING TESTS

Final Report:

Settling Properties of Fine-Grained Sediments: Bayou De Cade Marsh Creation and Ridge Restoration (TE-0138) (Fugro Project No. 04.55174066)

Submitted to:

Samuel M. Bryant, P.E. Vice President Fugro USA Land, Inc. 4233 Rhoda drive Baton Rouge, LA 70816 Phone: (225) 292-5084

Email: SBryant@fugro.com

Submitted by:

William M. Moe, Ph.D., P.E. Principal and Project Manager SCTCS Group LLC LBTC, Building 3000 8000 Innovation Park Drive Baton Rouge, LA 70820 Phone: (225) 803-3945

Pnone: (225) 803-3945 Email: wmoe@sctcs.com

June 6, 2018



1.0 Introduction, Scope, and Objectives

The objective of the testing reported here was to evaluate the settling properties of fine-grained sediments which may be hydraulically dredged in support of the Bayou De Cade Marsh Creation and Ridge Restoration (TE-0138) project (Fugro Project No. 04.55174066).

2.0 Experimental Procedures and Results

2.1 Materials Provided for Testing

Two composited sediment samples, each comprised of sediment from three separate borings in the proposed dredging area, were provided by Fugro USA Land, Inc. for pilot-scale settling column testing (see Appendix A for chain of custody forms).

Table 1. Sediment core samples used to prepare fine-grained sediment slurry for pilot-scale settling column testing

Composited Sediment Boring IDs
B-10, B-12, B-13
B-11, B-14, B-15

A five-gallon bucket of water from the proposed dredging area was also provided by Fugro USA Land, Inc. for laboratory testing. The salinity of the water sample, measured gravimetrically with drying at 180 °C¹, was 0.39 parts per thousand (ppt) indicative of a freshwater environment.

As requested by Fugro USA Land, Inc., a separate settling column test was conducted using each of the composited sediment samples. Testing procedures and results from each of the two tests are presented in the following sections.

2.2 Pilot-Scale Settling Column Test Results for Composite of Sediment from Boring ID Numbers B-10, B-12, and B-13

The first settling column test utilized sediment composited from boring ID numbers B-10, B-12, and B-13. Slurry was prepared by mixing homogenized sediment from the three borings with tap water supplemented with a small amount of synthetic sea salts (Instant Ocean) to match the average salinity of the site water sample [salinity of 0.39 parts per thousand (ppt)]. Slurry containing the fine-grained fraction of sediments was obtained by thoroughly mixing the slurry and then allowing coarse grained materials (e.g., sand and shells), to separate by differential settling as described in the US Army Corps of Engineers Manual No. 1110-2-5027¹. Preliminary solids concentrations measured in the fine-grained sediment slurry revealed that the particulate concentration was below the initial target concentration of 150 g/L. In consultation with Fugro, a decision was made to proceed with testing at the highest fine-grained particulate concentration that could be achieved with the materials provided.

The fine-grained sediment slurry was transferred to a second mixing barrel, thoroughly mixed, and then loaded into a large-scale (8.0 inch ID) column while mixing with air sparging as described in the US Army Corps of Engineers Manual No. 1110-2-5027¹. Solids concentrations in the slurry at the start of the settling test were measured in samples collected along the height of the column at one foot intervals (see Table B1 in Appendix B for tabulated data). The average particulate concentration at the start of the settling test was 71.0 g/L.

A readily visible sediment-water interface was observed less than one hour after the start of the settling test, indicating zone settling. The height of the sediment-water interface above the bottom of the column was measured and recorded over a period lasting more than 30 days as depicted in Figure 1 (see Table C1 in Appendix C for tabulated data). As shown in Figure 1, zone settling was observed during the first portion of the settling test, followed by compression settling thereafter.




Figure 1. Interface height as a function of time during the pilot-scale settling test with composite of sediment from borings B-10, B-12, and B-13.

Interface heights from the first 90 hours of the settling test, during which zone settling was observed, are depicted separately in Figure 2. A linear regression was performed for settling data in this time interval with the resulting equation and correlation coefficient shown on the graph. The slope of the regression line, which corresponds to the zone settling velocity, was 0.0406 ft/hr (0.97 ft/day).




Figure 2. Interface height as a function of time during the zone settling portion of the pilot-scale settling test with composite of borings B-10, B-12, and B-13.

For the portion of the settling test during which compression settling was observed, the concentration in the settled solids at each time interval was calculated using the following equation (equation 3-11 in ref. 1).

$$C = \frac{C_o H_i}{H_t}$$

Where:

C = slurry suspended solids concentration at time t (g/L)

 C_o = initial slurry suspended solids concentration (g/L)

 H_i = initial slurry height (ft)

 H_t = height of the interface at time t (ft)

The corresponding particulate concentration in the settled sediment as a function of time during compression settling is depicted in Figure 3.




Figure 3. Concentration of settled solids as a function of time during the compression settling portion of the pilot-scale settling test with composite of borings B-10, B-12, and B-13.

For analysis of flocculent settling as described in the US Army Corps of Engineers Manual No. 1110-2-5027¹, water samples were collected from the clarified layer above the sediment-water interface for measurement of total suspended (TSS) following Standard Method 2450D². The first of these samples, collected 24 hours after the start of settling when the sediment-water interface was sufficiently below the uppermost sample port (height of 5.5 ft) to allow sample collection, had a TSS concentration of 740 mg/L. TSS concentrations decreased over time but remained above 100 mg/L after 176 hours (7.3 days) and above 50 mg/L even after 434 hours (18.1 days) settling. Tabulated data are provided in Table D1 in Appendix D.

2.3 Pilot-Scale Settling Column Test using Composite of Sediment from Boring ID Numbers B-11, B-14, and B-15

The second pilot-scale settling column test utilized sediment composited from boring ID numbers B-11, B-14, and B-15. Slurry was prepared by mixing homogenized sediment from the three borings with tap water supplemented with a small amount of synthetic sea salts (Instant Ocean) to match the average salinity of the site water sample [salinity of 0.39 parts per thousand (ppt)]. Slurry containing the fine-grained fraction of sediments was obtained by thoroughly mixing the slurry and then allowing coarse grained materials (e.g., sand and shells), to separate by differential settling as described in the US Army Corps of Engineers Manual No. 1110-2-5027¹. The fine-grained sediment slurry was transferred to a second mixing barrel, thoroughly mixed, and then loaded into a large-scale (8.0 inch ID) column while mixing with air sparging as described in the US Army Corps of Engineers Manual No. 1110-2-5027¹. Solids concentrations in the slurry at the start of the settling test were measured in samples collected along the height of the column at one foot intervals (see Table B2 in Appendix B for tabulated data). The average particulate concentration at the start of the settling test was 139.5 g/L.

A readily visible sediment-water interface was observed shortly (<2 hours) after the start of the settling test, indicating zone settling. The height of the sediment-water interface above the bottom of the column was measured and recorded over a period lasting more than 30 days as depicted in Figure 4 (see Table C2 in Appendix C for tabulated data). As shown in Figure 4, zone settling was observed during the initial portion of the settling test, followed by compression settling.




Figure 4. Interface height as a function of time during the pilot-scale settling test with fine grained sediment prepared using a composite of sediment from borings B-11, B-14, and B-15.

Data from the first 60 hours of the settling test are depicted separately in Figure 5. A linear regression was performed for settling data in the time interval of 3 to 60 hours (during which zone settling was observed) with the resulting equation and correlation coefficient shown on the graph. The slope of the regression line, which corresponds to the zone settling velocity, was 0.047 ft/hr (1.13 ft/day).




Figure 5. Interface height as a function of time during the zone settling portion of the pilot-scale settling test with composite of borings B-11, B-14, and B-15.

For the portion of the settling test during which compression settling was observed, the concentration in the settled solids at each time interval was calculated as described previously (using equation 3-11 in ref. 1). The corresponding suspended solids concentration as a function of time during compression settling is depicted in Figure 6.




Figure 6: Concentration of settled solids as a function of time during the compression settling portion of the pilot-scale settling test with composite of borings B-11, B-14, and B-15.

For analysis of flocculent settling as described in the US Army Corps of Engineers Manual No. 1110-2-5027¹, water samples were collected from the clarified layer above the sediment-water interface for measurement of total suspended (TSS) following Standard Method 2450D². The first of these samples, collected 24 hours after the start of settling, had a TSS concentration of 180 mg/L. Concentrations decreased over time, and all elevations sampled (i.e., water from all ports above the sediment-water interface) had TSS concentrations <100 mg/L after 96 hours (4 days) and <50 mg/L after 336 hours (14 days) settling time. Tabulated data are provided in Table D2 in Appendix D.

2.4 Data Comparisons

For comparison purposes, the settling behavior observed during the zone settling interval for composited sediment from borings B-10, B-12, and B-13 (C_o =71.0 g/L)] is shown along with zone settling data collected during testing of composited sediment from borings B-11, B-14, and B-15 (C_o = 139.5 g/L). As shown in Figure 7, the zone settling behavior was similar for both samples but with slightly faster zone settling with the B-11, B-14, and B-15 composite (0.0470 ft/hr, 1.13 ft/day) than the B-10, B-12, and B-13 composite (0.0406 ft/hr, 0.97 ft/day).




Figure 7: Interface height as a function of time during the zone settling portion of the two pilot-scale settling column tests.

Also for comparison purposes, the compression settling behavior of the settled solids in the two pilot-scale settling column tests is shown below in Figure 8. As shown in the figure, the two composited sediment samples exhibited markedly different compression settling, with the fine-grained sediments from the B-11, B-14, and B-15 composite compacting to a much higher solids concentration than the B-10, B-12, and B-13 composite.




Figure 8: Concentration of settled solids as a function of time during the compression settling portion of the pilot-scale settling tests conducted with fine-grained sediment slurry.

3.0 References

- [1] US Army Corps of Engineers (1987) Engineering and Design Confined Disposal of Dredged Material, Engineer Manual No. 1110-2-5027.
- [2] American Public Health Association (1998) *Standard Methods for the Examination of Water and Wastewater*, 20th Edition, American Water Works Association, Water Pollution Control Federation, Washington, DC.

Appendix A

F517 406(p	Project Name	BI	00				Local			_				
Sample ID (Fugro Lab/Client Sample ID)	Date	Time	Sample Container (Size/Type)	Sample Ty Soil,	rpe (liquid, etc.)	Preser- vative	A			s Re				Comments
B-10	4/27			50	(X							
2 B 0-2 2-4 4-5.5				1										
2-4														
6-7.5														
8-10 8-10(2)														
8-12														
W B														
5-2 0-2														
4-6														
6-7,5					/			1	1			1		
8-10	1											1		
			-					-	+				+	
							-	+	+	-	+	+	+	
								1	1	1	1	1	_	
Relinquished By:		Date	Time		R	eceived By	:							Analyses:
74/11		4170/18	10:45	We	Rea_	mae							A	Col. Jothling
											-		В	
								-	-		-		C	-
			Remarks	1	of 3								E	
		-	Kemarks										F	

Fugro Consultants, Inc. 4233 Rhoda Dr., Baton Rouge, LA 70816 Telephone 225.292.5084

G



Port 4482

Name B	Sample Container (Size/Type)	Sample Type (liquid, Soil, etc.)	Preser- vative	A			s Red			-	Comments
	Container	Soil, etc.)		A							Comments
27		Soil			-	C	D	E	F	G	
		1		×					-		
	_										
										-	
				+							
				-	-						
				-	-	-					
					-						
				1							
				1				L			
		V									
Data	Time		eceived Ry	r				7	Г		Analyses:
									A		Col Sofflin
											3
					-			-			-
	Domesto	2 AF	3								-
	Date 4/30/14	Date Time	Date Time R 4/35/14 10:45 William 9	Date Time Received By 4/30/14 10:45 William Mae	Date Time Received By: 4/30/14 10:45 William Mae	Date Time Received By: 4/30/14 10:45 William Mae	Date Time Received By: 4/30/14 10:45 William Mae	Date Time Received By: 4/30/14 10:45 William Mae	Date Time Received By: 4/30/14 10:45 William Mose	Date Time Received By: 4/35/14 10:45 William Muse B	Date Time Received By: 4/30/14 10:45 William Mae A B C D

White - Orginal Yellow - DFR Pink - Lab Binder Gold - Deliverer

ect No. 5517 4066	Projec	t Name	Bi	DC				Loca	tion						
Sample ID ugro Lab/Client Sample ID)	D	ate	Time	Sample Container (Size/Type)		le Type (liquid, Soil, etc.)	Preser- vative	A	Ana	lyse C	s Re	que:	sted F	G	Comments
5-15	4	27			5	011		×							
1 B						1									
2-4(2)															
465															
-8 6-8															
-10 g-10															
_															
-11														П	
0-2 (A6C,D)								+							
24 (A,E)								+					\vdash	Н	
6 4-6 8 6-8	-							+	H				-	H	
0 8-10		,				,		+	-	-		H	H		
	*1	-			1	V		+	-						
011															
Relinguished By:			Date	Time		Re	ceived By:					1	Г		Analyses:
01110		1	1/30/10	10:45	2/	llin m	e						A		Analyses:
		-											8		- 3
		-										-	C		
				Remarks		3 = 3						-	D		

Appendix B

Table B1. Particulate concentrations measured in samples collected from side ports at the start (t=0) of the pilot-scale settling column test using composited sediment from borings B-10, B-12, and B-13.

Port height (ft) ^a	Particulate Conc. (g/L)
1.0	72.1
2.0	70.5
3.0	70.5
4.0	70.7
5.0	71.1
6.0	71.4
Average	71.0

^a As measured from the bottom of the column

Table B2. Particulate concentrations measured in samples collected from side ports at the start (t=0) of the pilot-scale settling column test using composited sediment from borings B-11, B-14, and B-15.

Port height (ft) ^a	Particulate Conc. (g/L)
1.0	140.0
2.0	140.0
3.0	139.3
4.0	139.6
5.0	138.7
6.0	139.1
Average	139.5

^a As measured from the bottom of the column

Appendix C

Table C1. Interface height as a function of time during the pilot-scale column settling test using composited sediment from B-10, B-12, and B-13.

The height of the sediment-water interface above the bottom of the column was recorded as a function of time as summarized in the table below.

Elapsed	Elapsed	Solids Interface	Head	Settled Solids
Time (hr)	Time (days)	Height (ft)	height (ft)	Conc. (g/L) ^a
0.00	0.000	6.000	6.000	71.0
0.88	0.037	5.992	6.000	71.1
1.15	0.048	5.988	6.000	71.1
1.45	0.060	5.979	6.000	71.2
1.90	0.079	5.975	6.000	71.3
2.18	0.091	5.967	6.000	71.4
2.55	0.106	5.958	6.000	71.5
2.93	0.122	5.950	6.000	71.6
3.33	0.139	5.942	6.000	71.7
3.73	0.156	5.933	6.000	71.8
4.17	0.174	5.925	6.000	71.9
4.48	0.187	5.917	6.000	72.0
4.92	0.205	5.908	6.000	72.1
5.22	0.217	5.900	6.000	72.2
5.57	0.232	5.892	6.000	72.3
5.85	0.244	5.883	6.000	72.4
6.57	0.274	5.867	6.000	72.6
6.88	0.287	5.858	6.000	72.7
7.25	0.302	5.850	6.000	72.8
7.60	0.317	5.842	6.000	72.9
7.93	0.331	5.833	6.000	73.0
8.32	0.347	5.825	6.000	73.1
8.60	0.358	5.817	6.000	73.2
8.93	0.372	5.808	6.000	73.3
9.23	0.385	5.800	6.000	73.4
9.50	0.396	5.792	6.000	73.6
9.78	0.408	5.783	6.000	73.7
10.05	0.419	5.775	6.000	73.8

^a Calculated using equation 3-11 in ref. 1 based on the measured particulate concentrations at t=0 and the height of the sediment-water interface at each time interval.

Table C1. Continued from previous page

Elapsed	Elapsed	Solids Interface	Head	Settled Solids
Time	Time	Height	height	Conc.
(hr)	(days)	(ft)	(ft)	(g/L) ^a
10.33	0.431	5.767	6.000	73.9
10.67	0.444	5.758	6.000	74.0
10.95	0.456	5.750	6.000	74.1
11.23	0.468	5.742	6.000	74.2
11.83	0.493	5.725	6.000	74.4
12.10	0.504	5.717	6.000	74.5
23.08	0.962	5.317	6.000	80.1
24.05	1.002	5.275	5.983	80.8
26.92	1.122	5.154	5.983	82.7
27.80	1.158	5.117	5.983	83.3
28.70	1.196	5.079	5.983	83.9
29.42	1.226	5.050	5.983	84.4
30.23	1.260	5.017	5.975	84.9
34.18	1.424	4.850	5.975	87.8
38.10	1.588	4.688	5.975	90.9
47.33	1.972	4.300	5.975	99.1
48.43	2.018	4.254	5.975	100.1
53.70	2.238	4.000	5.975	106.5
58.78	2.449	3.750	5.975	113.6
71.43	2.976	3.150	5.975	135.2
72.45	3.019	3.108	5.867	137.1
76.07	3.169	2.933	5.867	145.2
82.95	3.456	2.592	5.867	164.4
95.45	3.977	2.304	5.867	184.9
98.47	4.103	2.275	5.783	187.3
121.22	5.051	2.158	5.783	197.4
149.42	6.226	2.100	5.704	202.9
175.32	7.305	2.063	5.621	206.5
193.88	8.078	2.042	5.529	208.7
216.43	9.018	2.023	5.529	210.6
252.28	10.51	1.996	5.442	213.4
298.33	12.43	1.963	5.442	217.1
335.43	13.98	1.942	5.442	219.4

 $^{^{\}rm a}$ Calculated using equation 3-11 in ref. 1 based on the measured particulate concentrations at t=0 and the height of the sediment-water interface at each time interval.

Table C1. Continued from previous page

Elapsed Time (hr)	Elapsed Time (days)	Solids Interface Height (ft)	Head height (ft)	Settled Solids Conc. (g/L) ^a
385.38	16.06	1.917	5.338	222.3
433.43	18.06	1.893	5.338	225.0
486.50	20.27	1.871	5.258	227.7
602.10	25.09	1.829	5.258	232.9
722.22	30.09	1.792	5.258	237.8

^a Calculated using equation 3-11 in ref. 1 based on the measured particulate concentrations at t=0 and the height of the sediment-water interface at each time interval.

Table C2. Interface height as a function of time during the pilot-scale column settling test using composited sediment from borings B-11, B-14, and B-15.

The height of the sediment-water interface above the bottom of the column was recorded as a function of time as summarized in the table below.

Floresed	Flancad	Solids Interface	Head	Settled
Elapsed Time	Elapsed Time	Height	height	Solids Conc.
(hr)	(days)	(ft)	(ft)	(g/L) ^a
0.00	0.000	6.000	6.000	139.5
1.52	0.063	5.996	6.000	139.6
1.72	0.072	5.996	6.000	139.6
1.93	0.081	5.992	6.000	139.7
2.33	0.097	5.983	6.000	139.9
2.87	0.119	5.975	6.000	140.1
3.45	0.144	5.967	6.000	140.3
3.65	0.152	5.958	6.000	140.5
3.82	0.159	5.950	6.000	140.7
4.12	0.172	5.942	6.000	140.9
4.50	0.188	5.933	6.000	141.1
4.67	0.194	5.925	6.000	141.3
4.87	0.203	5.917	6.000	141.5
5.07	0.211	5.908	6.000	141.7
5.32	0.222	5.900	6.000	141.9
5.60	0.233	5.892	6.000	142.1
5.90	0.246	5.883	6.000	142.3
6.12	0.255	5.875	6.000	142.5
6.28	0.262	5.867	6.000	142.7
6.42	0.267	5.858	6.000	142.9
6.60	0.275	5.850	6.000	143.1
7.17	0.299	5.825	6.000	143.7
7.40	0.308	5.817	6.000	143.9
7.58	0.316	5.808	6.000	144.1
7.78	0.324	5.800	6.000	144.3
8.15	0.340	5.783	6.000	144.7
8.58	0.358	5.767	6.000	145.1
8.98	0.374	5.750	6.000	145.6
9.17	0.382	5.742	6.000	145.8
9.60	0.400	5.725	6.000	146.2

^a Calculated using equation 3-11 in ref. 1 based on the measured particulate concentrations at t=0 and the height of the sediment-water interface at each time interval.

Table C2. Continued from previous page.

		Solids		Settled
Elapsed	Elapsed	Interface	Head	Solids
Time	Time	Height	height	Conc.
(hr)	(days)	(ft)	(ft)	(g/L) ^a
9.78	0.408	5.717	6.000	146.4
10.07	0.419	5.708	6.000	146.6
10.52	0.438	5.692	6.000	147.1
10.83	0.451	5.683	6.000	147.3
11.30	0.471	5.667	6.000	147.7
11.75	0.490	5.650	6.000	148.1
12.28	0.512	5.633	6.000	148.6
12.68	0.528	5.617	6.000	149.0
23.62	0.984	5.117	6.000	163.6
24.55	1.023	5.067	5.983	165.2
27.48	1.145	4.917	5.983	170.2
28.45	1.185	4.867	5.983	172.0
29.28	1.220	4.825	5.983	173.5
29.90	1.246	4.792	5.983	174.7
30.87	1.286	4.742	5.958	176.5
34.72	1.447	4.538	5.958	184.5
38.67	1.611	4.325	5.958	193.5
47.83	1.993	3.842	5.958	217.9
48.83	2.035	3.792	5.892	220.7
54.17	2.257	3.563	5.892	234.9
59.30	2.471	3.442	5.892	243.2
71.93	2.997	3.350	5.892	249.9
83.50	3.479	3.296	5.817	254.0
95.98	3.999	3.258	5.817	256.9
121.78	5.074	3.196	5.754	261.9
149.93	6.247	3.150	5.692	265.7
175.88	7.328	3.117	5.629	268.6
194.42	8.101	3.096	5.567	270.4
216.98	9.041	3.075	5.567	272.2
252.82	10.53	3.046	5.492	274.8
298.87	12.45	3.017	5.492	277.5
335.98	14.00	2.996	5.492	279.4
385.88	16.08	2.974	5.442	281.4

^a Calculated using equation 3-11 in ref. 1 based on the measured particulate concentrations at t=0 and the height of the sediment-water interface at each time interval.

Table C2. Continued from previous page.

Elapsed Time (hr)	Elapsed Time (days)	Solids Interface Height (ft)	Head height (ft)	Settled Solids Conc. (g/L) ^a
433.93	18.08	2.954	5.442	283.3
487.00	20.29	2.933	5.363	285.3
602.65	25.11	2.896	5.363	289.0
722.77	30.12	2.863	5.363	292.4

 $^{^{\}rm a}$ Calculated using equation 3-11 in ref. 1 based on the measured particulate concentrations at t=0 and the height of the sediment-water interface at each time interval.

Appendix D

Table D1. Total suspended solids (TSS) concentrations measured above the sediment-water interface for characterization of flocculent settling during the pilot-scale column settling test using composited sediment from borings B-10, B-12, and B-13.

			Depth of	
Sample	Port	Head	Sample	
Extraction	Height	Height	Extraction	TSS
Time (hr)	(ft) ^a	(ft) ^a	(ft) ^b	(mg/L)
24	5.50	6.00	0.50	740
30	5.50	5.98	0.48	662
48	5.50	5.98	0.48	364
48	5.00	5.98	0.98	420
48	4.50	5.98	1.48	731
72	5.50	5.98	0.48	252
72	5.00	5.98	0.98	258
72	4.50	5.98	1.48	276
72	4.00	5.98	1.98	366
72	3.50	5.98	2.48	531
96	5.50	5.87	0.37	148
96	5.00	5.87	0.87	200
96	4.50	5.87	1.37	210
96	4.00	5.87	1.87	234
96	3.50	5.87	2.37	240
96	3.00	5.87	2.87	264
96	2.50	5.87	3.37	338
122	5.50	5.78	0.28	89
122	5.00	5.78	0.78	171
122	4.50	5.78	1.28	179
122	4.00	5.78	1.78	180
122	3.50	5.78	2.28	180
122	3.00	5.78	2.78	188
122	2.50	5.78	3.28	196
150	5.50	5.70	0.20	59
150	5.00	5.70	0.70	112
150	4.50	5.70	1.20	137
150	4.00	5.70	1.70	142
150	3.50	5.70	2.20	143
150	3.00	5.70	2.70	143
150	2.50	5.70	3.20	147

^a As measured from the bottom of the column; ^b Relative to the top liquid level

 Table D1. Continued from previous page

			Depth of	
Sample	Port	Head	Sample	TCC
Extraction Time (hr)	Height (ft) ^a	Height (ft) ^a	Extraction (ft) ^b	TSS (mg/L)
176	5.50	5.62	0.12	29
176	5.00	5.62		101
			0.62	101
176	4.50	5.62	1.12	
176	4.00	5.62	1.62	109
176	3.50	5.62	2.12	113
176	3.00	5.62	2.62	117
176	2.50	5.62	3.12	119
217	5.50	5.53	0.03	27
217	5.00	5.53	0.53	77
217	4.50	5.53	1.03	78
217	4.00	5.53	1.53	86
217	3.50	5.53	2.03	93
217	3.00	5.53	2.53	95
217	2.50	5.53	3.03	94
336	5.00	5.44	0.44	28
336	4.50	5.44	0.94	60
336	4.00	5.44	1.44	65
336	3.50	5.44	1.94	65
336	3.00	5.44	2.44	69
336	2.67	5.44	2.78	70
336	2.00	5.44	3.44	72
434	5.00	5.34	0.34	26
434	4.50	5.34	0.84	35
434	4.00	5.34	1.34	54
434	3.50	5.34	1.84	59
434	3.00	5.34	2.34	60
434	2.50	5.34	2.84	62
434	2.00	5.34	3.34	63

^a As measured from the bottom of the column

^b Relative to the top liquid level

Table D2. Total suspended solids (TSS) concentrations measured above the sediment-water interface for characterization of flocculent settling during pilot-scale column settling test using composited sediment from borings B-11, B-14, and B-15.

Sample Extraction	Port Height	Head Height	Depth of Sample Extraction (ft) ^b	TSS
Time (hr)	(ft) ^a	(ft) ^a		(mg/L)
24	5.50	6.00	0.50	188
30	5.50	5.98	0.48	116
30	5.00	5.98	0.98	182
48	5.50	5.96	0.46	68
48	5.00	5.96	0.96	80
48	4.50	5.96	1.46	116
48	4.00	5.96	1.96	283
72	5.50	5.89	0.39	67
72	5.00	5.89	0.89	73
72	4.50	5.89	1.39	75
72	4.00	5.89	1.89	88
72	3.50	5.89	2.39	124
96	5.50	5.82	0.32	51
96	5.00	5.82	0.82	69
96	4.50	5.82	1.32	72
96	4.00	5.82	1.82	73
96	3.50	5.82	2.32	89
122	5.50	5.75	0.25	26
122	5.00	5.75	0.75	54
122	4.50	5.75	1.25	60
122	4.00	5.75	1.75	61
122	3.50	5.75	2.25	75
150	5.50	5.69	0.19	<25°
150	5.00	5.69	0.69	50
150	4.50	5.69	1.19	52
150	4.00	5.69	1.69	53
150	3.50	5.69	2.19	59

^a As measured from the bottom of the column

^b Relative to the top liquid level

^c The mass of dry residue retained on the filter was less than 2.5 mg (the minimum required for an acceptable analysis). The result is reported here as <25 mg/L [calculated as the minimum residue mass required for acceptable analysis, 2.5 mg, divided by the sample volume filtered (0.10 L)].

Table D2. Continued from previous page

Sample Extraction Time (hr)	Port Height (ft) ^a	Head Height (ft) ^a	Depth of Sample Extraction (ft) ^b	TSS (mg/L)
176	5.50	5.63	0.13	<25°
176	5.00	5.63	0.63	32
176	4.50	5.63	1.13	52
176	4.00	5.63	1.63	56
176	3.50	5.63	2.13	57
217	5.50	5.57	0.07	<25°
217	5.00	5.57	0.57	34
217	4.50	5.57	1.07	54
217	4.00	5.57	1.57	55
217	3.50	5.57	2.07	54
336	5.00	5.49	0.49	<25°
336	4.50	5.49	0.99	33
336	4.00	5.49	1.49	37
336	3.50	5.49	1.99	47
434	5.00	5.44	0.44	<25°
434	4.50	5.44	0.94	27
434	4.00	5.44	1.44	28
434	3.50	5.44	1.94	31
434	3.00	5.44	2.44	32

^a As measured from the bottom of the column

^b Relative to the top liquid level

^c The mass of dry residue retained on the filter was less than 2.5 mg (the minimum required for an acceptable analysis). The result is reported here as <25 mg/L [calculated as the minimum residue mass required for acceptable analysis, 2.5 mg, divided by the sample volume filtered (0.10 L)].