

**ADDENDUM 1 TO BID DOCUMENTS FOR THE
BAYOU BONFOUCA MARSH CREATION PROJECT (PO-104)**

ST. TAMMANY PARISH, LOUISIANA



LOUISIANA COASTAL PROTECTION AND RESTORATION AUTHORITY

May 13, 2016

**ADDENDUM 1 TO BID DOCUMENTS
BAYOU BONFOUCA MARSH CREATION PROJECT (PO-104)**

The interpretations, corrections or changes in this addendum supersede the requirements in the Bid Documents dated on 2/29/16. The Successful Bidder shall be issued a revised set of Contract Documents.

Bidders shall acknowledge receipt of this addendum in the Louisiana Uniform Public Work Bid Form.

I. CPRA Response to Bidder Questions:

1. **Question:** Sheet 13 of the Plans shows the locations for borings B1 through B14 and B14-1. Are the boring logs available for review?

Response: Note 4 on Sheet 2 of the Plans states that the geotechnical report is available in the Specifications. Appendix H in the Specifications provides a link to the geotechnical report which can be pasted into any web browser. The boring logs are provided in the geotechnical report.

2. **Question:** Can the Specialty Classification for Dredging be included in the Licensure Classifications?

Response: Refer to revision in II.1 and III.1.

II. Revisions to Specifications:

1. **Advertisement for Bids:** The licensure classification requirement has been modified from “Heavy Construction” to “Major Classification: Heavy Construction, and/or Specialty Classification: Dredging”.

III. Revisions to Plans:

2. **Sheet 1:** The licensure classification requirement has been modified from “Major Classification: Heavy Construction” to “Major Classification: Heavy Construction, and/or Specialty Classification: Dredging”.
3. **Sheet 9:** The Earthen Containment Dike and Borrow Area Geometries table has been modified to include the following geometry for Earthen Containment Dike 7:

EARTHEN CONTAINMENT DIKE (ECD) AND BORROW AREA GEOMETRIES								
ECD	MARSH CREATION AREA	DIKE			BORROW			
		CREST WIDTH (FT)	CREST HEIGHT (FT)	SIDE SLOPES (RISE:RUN)	DIKE OFFSET (FT)	TROUGH WIDTH (FT)	TROUGH DEPTH (FT)	SIDE SLOPES
7	2	5	4.2 (MAX)	1:3	25 (MIN)	VARIES	10 (MAX)	1:3